

TPLINK CPE210 HOTSPOT WIFI 300MBPS EXT. 2,4GHZ IPX5 -30°/70°



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : TP-LINK

Part number : CPE210

Caractéristiques :

5 GHz : N

Design :

Certification : - FCC/UL/IC/GS/PSB/C-tick/SAA/S-Mark/KC-mark - RoHS, IPX5

2:4 GHz : Y

AC input frequency : 50/60 Hz

AC input voltage : 100 - 240 V

Antenna features : Integrated antenna

Antenna gain level (max) : 9 dBi

Antenna type : Internal

Antennas quantity : 1

Bandwidth : 2.4 GHz

Built-in processor : Y

Cables included : AC

Compatible operating systems : Microsoft Windows 98SE, NT, 2000, XP, Vista or Windows 8, Windows 7, MAC OS, NetWare, UNIX or Linux.

Depth : 79 mm

Ethernet LAN (RJ-45) ports : 1

Flash memory : 8 MB

Frequency band : 2.4 - 2.483 GHz

Harmonized System (HS) code : 85176990

Height : 60 mm

Input current : 0.8 A

Internal memory : 64 MB

International Protection (IP) code : IPX5

LED indicators : Y

| |
|--|
| MAC address filtering : Y |
| Management platform : Pharos Control |
| Management protocols : TDMA |
| Maximum data transfer rate : 300 Mbit/s |
| Maximum data transfer rate (2.4 GHz) : 300 Mbit/s |
| Maximum outdoor range : 5000 m |
| MIMO : Y |
| MIMO type : Multi User MIMO |
| Mounting kit : Y |
| Networking standards : IEEE 802.11b, IEEE 802.11g, IEEE 802.11n |
| Operating relative humidity (H-H) : 10 - 90% |
| Operating temperature (T-T) : -30 - 70 °C |
| Output current : 1 A |
| Output voltage : 24 V |
| Placement : Wall |
| Power consumption (max) : 10.5 W |
| Power over Ethernet (PoE) : Y |
| Processor frequency : 560 MHz |
| Processor model : Qualcomm Atheros |
| Product colour : White |
| Receiver sensitivity : 802.11b: 11M: -95dBm, 5.5M: -96dBm, 2M: -96dBm, 1M: -96dBm -802.11g: 54M: -79dBm, 48M: -80dBm, 36M: -84dBm, 6-24M: -88dBm 802.11n: MCS15: -76dBm, MCS14: -78dBm, MCS13: -80dBm, MCS12: -84dBm, MCS11: -87dBm, MCS10: -91dBm, MCS9: -93dBm, MCS8: -96dBm, MCS7: -76dBm, MCS6: -78dBm, MCS5: -80dBm, MCS4: -84dBm, MCS3: -87dBm, MCS2: -91dBm, MCS1: -93dBm, MCS0: -96dBm |
| Reset button : Y |
| Security algorithms : 64-bit WEP, 128-bit WEP, 152-bit WEP, SSID, TKIP, WPA, WPA-PSK, WPA2, WPA2-PSK |
| Storage relative humidity (H-H) : 5 - 95% |
| Storage temperature (T-T) : -40 - 70 °C |
| Web-based management : Y |
| Width : 224 mm |