

BOSCH NBN-50051-V3



DESCRIPTION

- DINION IP 5000 MP
- Stylish indoor network camera
- 5MP for highly detailed images
- Intelligent Dynamic Noise Reduction reduces bandwidth and storage requirements by up to 50%
- SD card slot for local recording
- FTP, Dropbox and e-mail alarms

TECHNICAL CHARACTERISTICS

Brand : BOSCH

Part number : NBN-50051-V3

Représentation / réalisation :

Type : IP security camera

Vidéo :

Full HD : Y

Connectivité :

Interface : RJ-45

Certification : CE, FCC, UL, cUL, C-tick, CB, VCCI, CSA

Active tampering alarm : Y

Alarm input/output : Y

Alert notification type : E-mail

Audio formats supported : AAC, G.711

Audio system full duplex : Y

Built-in HDD : N

Built-in microphone : Y

Cabling technology : 10/100Base-T(X)

Camera shutter type : Electronic

Card reader integrated : Y

Compatible memory cards : MicroSD (TransFlash), MicroSDXC

Connectivity technology : Wired

Day/night mode : Y

DC output voltage : 12
Depth : 55 mm
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Firmware upgradeable : Y
Flip & mirror : Y
Form factor : Box
Height : 113 mm
HTTPS encryption : Y
Image quality adjustment : Brightness, Contrast, Saturation
Maximum memory card size : 2000 GB
Maximum resolution : 2592 x 1944 pixels
Minimum illumination : 0.05 lx
Mounting type : Wall
Noise reduction : Y
Number of cameras : 1
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -30 - 50 °C
Optical sensor size : 25.4 / 3 mm (1 / 3»)
Output impedance : 75
Placement supported : Indoor
Power consumption : 300 mA
Power consumption (typical) : 3.6 W
Privacy masking : Y
Product colour : Black
Security algorithms : 3DES, DES, HTTPS, SNMP, SSL/TLS
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) : 50 dB
Storage temperature (T-T) : -40 - 70 °C
Supported graphics resolutions : 320 x 240, 640 x 480 (VGA), 1024 x 768 (XGA), 1440 x 1080, 2592 x 1944
Supported network protocols : IPv4, IPv6, UDP, TCP, HTTP, HTTPS, RTP/ RTCP, IGMP V2/V3, ICMP, ICMPv6, RTSP, FTP, Telnet, ARP, DHCP, APIPA (Auto-IP, link local address), NTP (SNTP), SNMP (V1, MIB- II), 802.1x, DNS, DNSv6, DDNS (DynDNS.org, selfHOST.de, no-ip.com), SMTP, iSCSI, UPnP (SSDP), DiffServ (QoS), LLDP, SOAP, Dropbox, CHAP, digest authentication
Supported video modes : 240p, 480p, 1080p
Time stamp overlay : Y
Total megapixels : 5 MP
Video compression formats : H.264, M-JPEG
Video formats supported : H.264, M-JPEG
Voice codecs : G.711
Weight : 550 g
White balance : Auto, Manual
Wide Dynamic Range (WDR) : Y
Width : 64 mm
Wi-Fi : N