

# Eaton Ellipse PRO 650 IEC



## DESCRIPTION

## TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : ELP650IEC

AC outlet types : C13 coupler

AC outlets quantity : 4 AC outlet(s)

Automatic battery test : Y

Battery technology : Sealed Lead Acid (VRLA)

Cold start : Y

Depth : 285 mm

Display type : LCD

Emergency Power Off (EPO) : Y

Ethernet LAN (RJ-45) ports : 1

Form factor : Tower

Harmonized System (HS) code : 85078000

Height : 260 mm

Hot-swap battery : N

Input frequency : 50/60 Hz

Input operation voltage (max) : 285 V

Input operation voltage (min) : 150 V

LED indicators : Y

Modem (RJ-11) ports : 1

Nominal input voltage : 230 V

Output frequency : 50 Hz

Output operation voltage (max) : 240 V

Output operation voltage (min) : 220 V

Output power : 400 W

Output power capacity : 0.65 kVA

Power plug : C14 coupler

Product colour : Black

Rack capacity : 2U

Safety : IEC/EN 62040-1, IEC/EN 62040 -2, CB, CE

Surge protection : Y

Surge protection features : Fax, Modem, Network, Telephone

Typical backup time at half load : 9 min

UPS topology : Line-Interactive

USB 2:0 ports quantity : 1

Weight : 6.6 kg

Width : 82 mm