

EKIVALAN U/FTP CAT6A SOLID CABLE GREY LSZH CPR Dca - 500M



DESCRIPTION

Category 6A U/FTP Dca shielded certified cable 500 MHz

Specifications:

- AWG : 23/1
- Shielding : pair per pair shielding by aluminium foil + drain wire
- OD: 7.5 mm
- Pair insulation : HDPE
- Impedance : 100 Ohms
- Conductor : 100 % oxygen-free copper
- Compliant with the following standard : EIA / TIA 568 C2 - ISO /IEC 11801
- Jacket : LSZH, CPR-certified, Euroclass Dca -s1 -d1 -a1
- DELTA certified cable in the DEXLAN CAT6A U/FTP Permanent Link
- Replacement of the item 612039

TECHNICAL CHARACTERISTICS

Brand : EKIVALAN

Part number : MCC6AUF4PLGD01 T500

Main features :

Connection type : Cable

Solid wire/ stranded wire : Solid wire

Signal : Network

A Connector type : without connector

B Connector type : without connector

Category : Cat. 6A

Shielding : U/FTP

Length (m) : 500

Colour : Grey

Secondary features :

LSZH : Yes

Conductor : Copper

Wiring standards : ANSI/EIA/TIA 568 / ISO/IEC 11801