



DESCRIPTION

Enhanced Gamma Selection

Selectable gamma curves visually optimise different kinds of images. The AG Neovo specialised image settings enhance colour, brightness, sharpness and contrast ratio, allowing the X-Series to improve the light, shadows and colour balance of videos.

Versatility, Productivity and Compatibility

Visualize critical data and engage with multiple video sources and PC applications with versatile connectivity options, including DisplayPort and HDMI, and PiP/PbP to increase productivity and efficiency. Selectable aspect ratio and zoom functions provide compatibility with different video sources.

High Reliability

Designed for 24/7 operation, these durable metal-housed displays protected with NeoV Optical Glass take advantage of superior components to ensure a long product lifetime.

TECHNICAL CHARACTERISTICS

Brand : NEOVO
Part number : X-17E
Connectivité :
HDMI : Y
Design :
Certification : CB, CE, RoHS, WEEE, REACH, EuP/Erp
3D : N
AC adapter included : Y
Audio input : Y
Backlight type : LED
Built-in camera : N
Built-in speaker(s) : Y
Built-in USB hub : N
Cable lock slot : Y
Cable lock slot type : Kensington
Cables included : AC, Audio (3.5mm), VGA

Contrast ratio (typical) : 1000:1
Depth (with stand) : 175 mm
Display brightness (typical) : 250 cd/m ²
Display diagonal : 43.2 cm (17»)
Display number of colours : 16.78 million colours
Display resolution : 1280 x 1024 pixels
Display technology : LED
DisplayPort version : 1.2a
DisplayPorts quantity : 1
DVI port : Y
DVI-D ports quantity : 1
Flicker-free technology : Y
HD type : SXGA
HDMI ports quantity : 1
HDMI version : 1.4
Height (with stand) : 398.2 mm
Height adjustment : N
Horizontal scan range : 15 - 81 kHz
Market positioning : Medical
Native aspect ratio : 5:4
Number of speakers : 2
Operating relative humidity (H-H) : 10 - 90%
Operating temperature (T-T) : 0 - 40 °C
Package depth : 225 mm
Package height : 506 mm
Package weight : 7.5 kg
Package width : 506 mm
Panel mounting interface : 75 x 75,100 x 100 mm
Panel type : TFT
Picture-in-Picture : Y
Pixel pitch : 0.264 x 0.264 mm
Power consumption (standby) : 0.5 W
Power consumption (typical) : 19 W
Product colour : Black
Quick start guide : Y
Response time : 3 ms
RMS rated power : 4 W
Screen shape : Flat
Stand included : Y
Storage relative humidity (H-H) : 5 - 95%
Storage temperature (T-T) : -20 - 60 °C
Supported graphics resolutions : 1280 x 1024 (SXGA)
Tilt angle range : 0 - 20°
Tiltable : Y
Touchscreen : N
Vertical scan range : 50 - 85 Hz
VESA mounting : Y
VGA (D-Sub) ports quantity : 1
Viewing angle, horizontal : 170°
Viewing angle, vertical : 160°
Weight (with stand) : 5.2 kg
Width (with stand) : 409.4 mm