

Hanwha camera 2MP ir bullet ir led 50 m XNO-6080RP/EX



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA

Part number : XNO-6080R

Représentation / réalisation :

Type : IP security camera

Réseau :

Bluetooth : N

Back Light Compensation (BLC) : Y

Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)

Built-in HDD : N

Camera shutter speed : 2 - 1/12000 s

Camera shutter type : Electronic

Card reader integrated : Y

Closest focusing distance : 0.5 m

Compatible memory cards : SD, SDHC, SDXC

Connectivity technology : Wired

Day/night mode : Y

Diameter : 9.1 cm

Ethernet interface type : Fast Ethernet

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1

Flip & mirror : Y

Focal length range : 2.8-12 mm

Form factor : Bullet

Frame rate : 30 fps

Highlight Compensation (HLC) : Y

Housing material : Aluminium

HTTPS encryption : Y

IK code : IK10
Infrared (IR) cut-off filter : Y
International Protection (IP) code : IP66
IP address filtering : Y
LED type : IR
Length : 368.6 mm
Lens viewing angle, diagonal : 142.1°
Lens viewing angle, horizontal : 119.5°
Lens viewing angle, vertical : 62.8°
Maximum aperture number : 1.4
Maximum memory card size : 512 GB
Maximum resolution : 1920 x 1080 pixels
Minimum aperture number : 3.6
Mounting type : Ceiling/wall
Networking standards : IEEE 802.1x, IEEE 802.3af
Night vision : Y
Night vision distance : 50 m
Number of cameras : 1
Number of effective pixels (H x V) : 1945 x 1097 pixels
Number of lenses : 1
Number of sensors : 1
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -40 - 65 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Placement supported : Outdoor
Power consumption (max) : 12 W
Power consumption (Power over Ethernet (PoE)) : 12.95 W
Power source type : DC, PoE
Privacy masking : Y
Product colour : Grey
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -50 - 60 °C
Streaming method : Multicast, Unicast
Supported network protocols : TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour
Total megapixels : 2 MP
Video compression formats : H.264, H.265, M-JPEG
Video motion detection : Y
Video streaming : Y
Voice codecs : G.711alaw, G.711ulaw, G.722.1, G.726, MP2L2
Weight : 2.18 kg
Wide Dynamic Range (WDR) : Y
Wi-Fi : N