



## DESCRIPTION

Optimized for use with the EX-1280C, EX-12AEC, and EX-440C, the EX-8ML Dante endpoint, is a convenient, cost effective solution for connecting up to 8 conferencing microphones over a single cat-5/6 cable. Whether used under a conference table, daisy-chained with other EX or endpoints, or standalone in a rack, the EX-8ML adds 8 high-quality microphone/line inputs, 8 GPI, and 16 GPO to your networked audio system. Autodiscovery, drag and drop programming, auto-routing routing, and simplified logic control in ControlSpace® Designer make configuring the EX-8ML easy. Tasks such as configuring microphone LED status and microphone mute actions are greatly simplified within ControlSpace Designer without requiring external control system programming.

## TECHNICAL CHARACTERISTICS

Brand : BOSE
Part number : 772045-0110
Balanced line input level : 20 dB
Built-in display : N
Channels quantity : 4 channels
DC input voltage : 12 V
Dynamic range : 115 dB
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
External power supply : Y
Frequency range : 20 - 20000 Hz
LED indicators : Power
Microphone included : N
Operating temperature (T-T) : 0 - 40 °C
Power consumption (typical) : 5.6 W
Product colour : Black
Rack mounting : N
Total Harmonic Distortion (THD) + noise : 0.01%