

Eaton 9PX 1500i RT2U Netpack Li-Ion



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : EATON
Part number : 9PX1500IRTN-L
Design :
Certification : IEC/EN 62040-2, FCC, CISPR22, CE, CB, TUV, cULus, EAC, RCM, KC
AC outlet types : C13 coupler
AC outlets quantity : 8 AC outlet(s)
Auto power off : Y
Battery technology : Lithium-Ion (Li-Ion)
Bypass : Internal
Cables included : Output power cable, Serial
Depth : 450 mm
Display type : LCD
Efficiency : 92.5%
Form factor : Rackmount/Tower
Harmonized System (HS) code : 85078000
Height : 86.5 mm
Hot-swap battery : Y
Input frequency : 40/70 Hz
Input operation voltage (max) : 276 V
Input operation voltage (min) : 176 V
Input power factor : 0.99
Noise level : 35 dB
Number of input phases : 1
Number of output phases : 1
Operating altitude : 0 - 3000 m
Operating relative humidity (H-H) : 0 - 96%
Operating temperature (T-T) : 0 - 40 °C

Output frequency : 50/60 Hz
Output operation voltage (max) : 240 V
Output operation voltage (min) : 200 V
Output power : 1500 W
Output power capacity : 1.5 kVA
Output power factor : 1
Output voltage Total Harmonic Distortion (THD) : 3%
Power plug : C14 coupler
Product colour : Black, Silver
Quick installation guide : Y
Rack capacity : 2U
Rack mount kit : Y
Safety : IEC/EN 62040-1, UL 1778, CSA 22.2
Serial interface : Y
Serial interface type : RS-232
Serial ports quantity : 1
Sustainability certificates : ENERGY STAR
UPS topology : Double-conversion (Online)
USB 2:0 ports quantity : 1
USB port : Y
Waveform : Sine
Weight : 15.9 kg
Width : 440 mm