



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : PANASONIC
Part number : WV-S1531LN
Représentation / réalisation :
Type : IP security camera
Système d'objectif :
Auto focus : Y
Vidéo :
Full HD : Y
Connectivité :
Interface : RJ-45
Certification : IEC62262, IK10
Alarm input/output : Y
Alert notification type : E-mail, Snapshot alert message
Analog signal format system : NTSC, PAL
Angle of rotation : 270°
Audio formats supported : AAC, ADPCM
Audio system : 2-way
Automatic gain control : Y
Built-in HDD : N
Cabling technology : 10/100Base-T(X)
Camera shutter speed : 1/30 - 1/10000 s
Card reader integrated : Y
Compatible memory cards : SD, SDHC, SDXC
Composite video out : 1
Connectivity technology : Wired
Day/night mode : Y
DC output voltage : 12

Depth : 337 mm
Diameter : 160 cm
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Focal length range : 2.8 - 10 mm
Form factor : Bullet
Frame rate : 60 fps
Headphone outputs : 1
Height : 99 mm
Housing material : Aluminium
Image quality adjustment : Brightness
Image stabilizer : Y
Infrared (IR) cut-off filter : Y
International Protection (IP) code : IP66
Languages support : German, English, Spanish, French, Italian, Japanese, Portuguese, Russian
LED type : IR
Lens viewing angle, horizontal : 112°
Lens viewing angle, vertical : 60°
Maximum aperture number : 1.6
Maximum memory card size : 128 GB
Maximum resolution : 2048 x 1536 pixels
Microphone in : Y
Mobile operating systems supported : Android, iOS
Mounting type : Ceiling/wall
Night vision : Y
Noise reduction : Y
Normal focusing range : 0.3 m
Number of cameras : 1
Number of languages : 9
Number of users : 14 user(s)
Operating relative humidity (H-H) : 10 - 100%
Operating temperature (T-T) : -40 - 60 °C
Optical sensor size : 25.4 / 3 mm (1 / 3»)
Optical zoom : 3.6x
Pan range : -100 - 100°
Placement supported : Indoor & outdoor
Power consumption : 750 mA
Power consumption (typical) : 9 W
Power over Ethernet (PoE) : Y
Power source type : PoE
Privacy masking : Y
Product colour : Silver
Protection features : Dust resistant, Water resistant
Removable IR-cut filter : Y
Security algorithms : FIPS 140-2
Sensor type : MOS
Supported graphics resolutions : 320 x 180, 320 x 240, 400 x 300, 640 x 360, 640 x 480 (VGA), 800 x 600 (SVGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2048 x 1536 (QXGA)
Supported network protocols : IPv6, IPv4, TCP/IP, UDP/IP, HTTP, HTTPS, RTSP, RTP, RTP/RTCP, FTP, SMTP, DHCP, DNS, DDNS, NTP, SNMP, UPnP, IGMP, ICMP, ARP, DiffServ,
Tilt angle range : -100 - 100°
Total megapixels : 3 MP
Video compression formats : H.264, H.265

Video motion detection : Y
Voice codecs : G.711, G.726
Web-based management : Y
White balance : ATW, AWC
Wide Dynamic Range (WDR) : Y
Width : 95 mm
Wi-Fi : N
Zoom capability : Y