

EPDU MI 0U (C14 10A 1P)16XC13



DESCRIPTION

New ePDU G3 Metered Input models feature best-in-class technologies, including $\pm 1\%$ billing grade accuracy, an advanced LCD pixel display, a hot-swap meter and the ability to daisy chain four ePDUs to share the same network connection and IP address.

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : EMIB03

Design :

Type : Single-phase

AC input frequency : 50 Hz

AC outlet types : C13 coupler

AC outlets quantity : 16 AC outlet(s)

Cable colour : Black

Cable length : 3 m

Cables included : LAN (RJ-45)

Depth : 1070 mm

Dimensions (WxDxH) : 52 x 1070 x 53 mm

Display : LCD

Ethernet LAN (RJ-45) ports : 1

Firmware upgradeable : Y

Firmware upgradeable via : Network, USB

Form factor : Rackmount

Height : 53 mm

LED indicators : Y

Management protocols : SNMP, Telnet

Maximum current : 10 A

Maximum input current per phase : 10 A

Maximum power : 2300 W

Mounting : Vertical

Nominal input voltage : 230 V

Nominal output voltage : 230 V

Operating temperature (T-T) : 0 - 60 °C

Output connections : 16 x C13

Package weight : 3.62 kg

PDU types : Metered

Power plug : C14 coupler

Product colour : Black

Rack capacity : 0U

Rack mount kit : Y

Rack mounting : Y

Sustainability certificates : RoHS

Weight : 2.62 kg

Width : 52 mm