

SONY- Signage screen FWD-65X80H/T1



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : SONY

Part number : FWD-65X80H/T1

Représentation / réalisation :

HDCP : Y

AC input frequency : 50/60 Hz

AC input voltage : 220 - 240 V

Ambient light sensor : Y

Audio formats supported : FLAC, LPCM, MP3, MP4, WAV, WMA

Bezel width (bottom) : 1.85 cm

Bezel width (side) : 1.5 cm

Bezel width (top) : 1.5 cm

Built-in processor : Y

Built-in speaker(s) : Y

Composite video in : 1

Contrast ratio (dynamic) : 500000:1

Contrast ratio (typical) : 1200:1

Depth : 340 mm

Depth (with stand) : 340 mm

Digital signal format system : DVB-C, DVB-S, DVB-S2, DVB-T, DVB-T2

Display brightness : 560 cd/m²

Display diagonal : 163.8 cm (64.5»)

Display diagonal (metric) : 164 cm

Display resolution : 3840 x 2160 pixels

Display technology : IPS

DVI port : N

Energy efficiency scale : A+++ to D

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1
Google applications : Google Chromecast
HD type : 4K Ultra HD
HDCP version : 2.3
HDMI input ports quantity : 4
HDMI ports quantity : 4
Height : 841 mm
Height (with stand) : 905 mm
Image formats supported : JPEG
Internal storage capacity : 16 GB
LED backlighting type : Direct-LED
Native aspect ratio : 16:9
Number of built-in speakers : 2
Operating hours (hours/days) : 18/7
Operating system installed : Android 9.0
Package weight : 30 kg
Panel mounting interface : 300 x 300 mm
Placement supported : Indoor
Power consumption (standby) : 0.5 W
Power consumption (typical) : 137 W
Product colour : Black
Product design : Digital signage flat panel
Purpose : Universal
Response time : 8 ms
RMS rated power : 20 W
USB port : Y
USB ports quantity : 2
VESA mounting : Y
Video formats supported : 3GPP, ASF, AVC, AVCHD, AVI, HEVC, MKV, MOV, MP4, MPEG1, MPEG2, MPEG2-PS, MPEG2-TS, MPEG4, VC-1, VP8, WEBM, WMV, XAVC, XVID
Viewing angle, horizontal : 178°
Viewing angle, vertical : 178°
Weight : 21.7 kg
Weight (with stand) : 22.6 kg
Width : 1462 mm
Width (with stand) : 1462 mm
Wi-Fi : Y