

Cambium base station ePMP 3000L 600 Mbps, up to 64 subscribers, detached antenna



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : CAMBIUM NETWORKS
Part number : C050910A223A
Caractéristiques :
5 GHz : Y
Modulation : 256-QAM, OFDM
Design :
Certification : EN 301 893 V2.1.1 (5.4 GHz), EN 302 502 V2.1.1 (5.8 GHz) Z8H-89FT0047 109W-0047
2:4 GHz : N
AC input voltage : 30 V
Antenna connector type : RP-SMA
Antenna features : Detachable antenna
Antenna type : External
Cabling technology : 10/100/1000Base-T(X)
Depth : 32 mm
Ethernet LAN (RJ-45) ports : 1
Ethernet LAN data rates : 100,1000 Mbit/s
Frequency band : 4.91 - 5.97 GHz
Harmonized System (HS) code : 85176990
Height : 223 mm
IGMP snooping : Y
International Protection (IP) code : IP68
Management protocols : HTTPS, SNMPv2c, SSH
MIMO : Y
MIMO type : Multi User MIMO
Networking standards : IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u
Number of connectors : 3
Operating temperature (T-T) : -30 - 60 °C

Placement : Wall
Power consumption (max) : 15 W
Power consumption (typical) : 12 W
Power over Ethernet (PoE) : Y
Product colour : White
Quality of Service (QoS) support : Y
Security algorithms : 128-bit AES, SSH
Supported protocols : IPv4/IPv6 , UDP, TCP, IP, ICMP, SNMPv2c, HTTPS, STP EN 301 893 V2.1.1 (5.4 GHz), EN 302 502 V2.1.1 (5.8 GHz) 109W-0047 Z8H-89FT0047
VLAN support : Y
Weight : 500 g
Width : 84 mm