

DAHUA- Camera DH-IPC-HDW3849H-AS-PV



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : DAHUA TECHNOLOGY
Part number : DH-IPC-HDW3849H-AS-PV
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : No
Certification : CE-LVD: EN 62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B
Adjustment shutter speed : Auto/Manual
Alarm input channels : 1
Alarm input/output : Yes
Alarm output channels : 1
Angle of rotation : 360°
Audio input channels : 1.0 channels
Audio output channels : 1.0 channels
Audio system : 2-way
Back Light Compensation (BLC) : Yes
Bit rate : 3 kbps - 16384 kbps
Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Built-in HDD : No
Built-in light : Yes
Built-in microphone : Yes
Built-in siren : Yes
Built-in speaker(s) : Yes
Camera pan control : Yes
Camera shutter speed : 1/3 - 1/100000 s
Camera shutter type : Electronic
Camera tilt control : Yes

Card reader integrated : Yes
Closest focusing distance : 1.5 m
Compatible memory cards : MicroSD (TransFlash)
Connectivity technology : Wired
Day/night mode : Yes
DC output voltage : 12
DC-in jack : Yes
Detect distance (wide) : 66 m
Diameter : 12.2 cm
Dynamic range : 120 dB
Ethernet interface type : Fast Ethernet
Ethernet LAN : Yes
Ethernet LAN (RJ-45) ports : 1
Field of view (FOV) angle : 125°
Fixed focal length : 3.6 mm
Fixed focus : Yes
Focal length range : 2.8 - 3.6 mm
Fog proof : Yes
Form factor : Dome
Frame rate : 30 fps
Gain control type : Auto
Height : 110.9 mm
Highlight Compensation (HLC) : Yes
Housing material : Metal
HTTPS encryption : Yes
Identify distance (wide) : 6.6 m
Intelligent Video Surveillance (IVS) system features : Tripwire, Face detection, Intrusion
International Protection (IP) code : IP67
IP address filtering : Yes
LED type : IR
Lens viewing angle, diagonal : 125°
Lens viewing angle, horizontal : 106°
Lens viewing angle, vertical : 55°
Management software : Smart PSS, DSS, DMSS
Manual : Yes
Maximum aperture number : 1
Maximum memory card size : 512 GB
Maximum resolution : 3840 x 2160 pixels
Minimum illumination : 0.0004 lx
Mirror : Yes
Mobile operating systems supported : Android, iOS
Mounting type : Ceiling
Network access storage (NAS) : Yes
Networking standards : IEEE 802.1x, IEEE 802.3af
Night vision : Yes
Night vision distance : 30 m
Noise reduction : Yes
Noise reduction technology : 3D noise reduction
Normal focusing range : 1.5 - 2.2 m
Number of cameras : 1
Number of illumination LEDs : 1
Number of lenses : 1
Number of sensors : 1

Number of users : 20 user(s)
Observe distance (wide) : 26.4 m
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : -40 - 60 °C
Optical sensor size : 25.4 / 2.7 mm (1 / 2.7»)
Package weight : 920 g
Pan range : 0 - 360°
Placement supported : Indoor & outdoor
Power consumption (max) : 10.1 W
Power consumption (Power over Ethernet (PoE)) : 5.8 W
Power consumption (typical) : 4.5 W
Power source type : DC, PoE
Privacy masking : Yes
Product colour : White
Progressive scan : Yes
Quality of Service (QoS) support : Yes
RAM capacity : 2000 MB
Recognize distance (wide) : 13.2 m
Region of Interest (ROI) encoding : Yes
ROM capacity : 256 MB
Security algorithms : HTTPS
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) : 56 dB
Smart IR : Yes
Streaming method : Multicast
Supported graphics resolutions : 352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD