



DESCRIPTION

Stylish edge-to-edge design makes the ProLite XU2292HSU perfect for multi-monitor set-ups. The IPS panel technology offers accurate and consistent colour reproduction with wide viewing angles. The 100Hz refresh rate together with FreeSync function provides an instant, tangible improvement in image smoothness. High contrast and brightness values mean the monitor will provide excellent performance for photographic and web design. Equipped with speakers, 2 port USB 3.2 hub, headphone socket, HDMI and DisplayPort connections, a blue light reducer function to reduce eye fatigue for optimal user comfort, make this monitor a great choice for both multi-monitor configuration and office applications.

TECHNICAL CHARACTERISTICS

Brand : IIYAMA

Part number : XU2292HSU-B6

Représentation / réalisation :

AMD FreeSync : Yes

Connectivité :

HDMI : Yes

HDCP : Yes

AC input frequency : 50/60 Hz

AC input voltage : 100 - 240 V

AMD FreeSync type : FreeSync

Built-in camera : No

Built-in speaker(s) : Yes

Built-in USB hub : Yes

Cable lock slot : Yes

Cable lock slot type : Kensington

Cable management : Yes

Contrast ratio (typical) : 1000:1

Depth (with stand) : 199.5 mm

Digital horizontal frequency : 30 - 115 kHz

Display brightness (typical) : 250 cd/m²

Display diagonal : 54.6 cm (21.5»)

Display diagonal (metric) : 55 cm

Display number of colours : 16.7 million colours
Display resolution : 1920 x 1080 pixels
Display surface : Matt
Display technology : LED
DisplayPorts quantity : 1
Energy consumption (SDR) per 1000 hours : 14 kWh
Energy efficiency class (HDR) : Not available
Energy efficiency class (SDR) : E
Flicker-free technology : Yes
HD type : Full HD
HDMI ports quantity : 1
Headphone out : Yes
Height (with stand) : 384 mm
Low Blue Light technology : Yes
Market positioning : Office
Maximum refresh rate : 100 Hz
Native aspect ratio : 16:9
Number of speakers : 2
On Screen Display (OSD) : Yes
Package depth : 131 mm
Package height : 420 mm
Package weight : 4.5 kg
Package width : 581 mm
Panel mounting interface : 100 x 100 mm
Panel type : IPS
Pixel pitch : 0.248 x 0.248 mm
Power consumption (off) : 0.3 W
Power consumption (standby) : 0.5 W
Power consumption (typical) : 14 W
Power supply type : Internal
Product colour : Black
Response time : 4 ms
RMS rated power : 2 W
Screen shape : Flat
Tilt adjustment : Yes
Tilt angle range : 21.5 - 3.5°
Touchscreen : No
USB hub version : 3.2 Gen 1 (3.1 Gen 1)
VESA mounting : Yes
Viewable size, horizontal : 26.8 cm
Viewable size, vertical : 47.6 cm
Viewing angle, horizontal : 178°
Viewing angle, vertical : 178°
Wall mountable : Yes
Weight (with stand) : 3 kg
Width (with stand) : 489.5 mm