

HANWHA- Camera ANO-L6082R



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : ANO-L6082R
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : No
Back Light Compensation (BLC) : Yes
Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Built-in HDD : No
Camera shutter type : Electronic
Card reader integrated : Yes
Closest focusing distance : 0.5 m
Compatible memory cards : MicroSD (TransFlash), SDHC
Connectivity technology : Wired
Day/night mode : Yes
Diameter : 7.8 cm
Dynamic range : 120 dB
Ethernet LAN : Yes
Ethernet LAN (RJ-45) ports : 1
Flash memory : 256 MB
Flip & mirror : Yes
Focal length range : 3,3 - 10 mm
Focus : Motorized
Form factor : Bullet
Housing material : Plastic
HTTPS encryption : Yes
Infra-red wavelength : 850 nm

Internal memory : 512 MB
Languages support : Simplified Chinese, Czech, German, Dutch, English, Spanish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Turkish
Length : 262 mm
Lens viewing angle, diagonal : 127 - 35°
Lens viewing angle, horizontal : 106 - 30°
Lens viewing angle, vertical : 55 - 17°
Maximum aperture number : 3.3
Maximum memory card size : 32 GB
Maximum resolution : 1920 x 1080 pixels
Minimum aperture number : 1.6
Mounting type : Ceiling/wall
Night vision : Yes
Night vision distance : 30 m
Noise reduction : Yes
Noise reduction technology : Smart Super Noise Reduction (SSNR)
Number of cameras : 1
Number of Privacy masking areas : 6
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : -30 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Placement supported : Indoor & outdoor
Power consumption (max) : 7 W
Power consumption (typical) : 5 W
Power source type : PoE
Privacy masking : Yes
Product colour : White
Security algorithms : EAP-LEAP, EAP-TLS
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 95%
Storage temperature (T-T) : -30 - 55 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour
Total megapixels : 2 MP
Video compression formats : H.264, H.265, M-JPEG
Video motion detection : Yes
Weight : 390 g
White balance : ATW, AWC, Indoor, Manual, Outdoor
Wide Dynamic Range (WDR) : Yes
Wi-Fi : No