

HANWHA IP camera XNB-6005



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : XNB-6005
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : N
Certification : CE, FC
AC input voltage : 24 V
Alarm input/output : Y
Audio detection : Y
Audio formats supported : G.711 -law, G.726
Audio input channels : 1
Audio output channels : 1 channels
Camera shutter speed : 1/12000 s
Camera shutter type : Electronic
Card reader integrated : Y
Compatible memory cards : SD, SDHC, SDXC
Connectivity technology : Wired
DC output voltage : 12
Depth : 147.8 mm
Ethernet interface type : 10 Gigabit Ethernet, 100 Gigabit Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Flip & mirror : Y
Form factor : Bullet
Frame rate : 60 fps
Height : 66.6 mm

Housing material : Plastic
HTTPS encryption : Y
IP address filtering : Y
Languages support : Simplified Chinese, Czech, German, Dutch, English, Spanish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish
LED indicators : Y
Mac operating systems supported : Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra
Maximum memory card size : 512 GB
Maximum resolution : 1920 x 1080 pixels
Minimum illumination : 0.0006 lx
Motion sensor : Y
Mounting type : Ceiling/wall
Night vision : Y
Number of cameras : 1
Number of effective pixels (H x V) : 1945 x 1097 pixels
Number of languages : 17
Number of users : 20 user(s)
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -10 - 55 °C
Optical sensor size : 25.4 / 2 mm (1 / 2»)
Package type : Box
Placement supported : Indoor & outdoor
Power consumption (max) : 9 W
Power consumption (Power over Ethernet (PoE)) : 8.5 W
Power source type : AC, DC, PoE
Product colour : Black, White
Progressive scan : Y
PTZ control : Y
PTZ modes : Digital PTZ, Preset point
Remotely operated : Y
Reset button : Y
RS-422 ports : 1
RS-485 ports : 1
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) : 50 dB
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -30 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)
Supported network protocols : TCP/IP,UDP/IP, RTP (UDP), RTP (TCP), RTCP,RTSP,NTP,HTTP,HTTPS, SSL/TLS,DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3 (MIB-2), ARP,DNS,DDNS,QoS, PIM-SM,UPnP, Bonjour
Total megapixels : 2.17 MP
USB port : Y
Video formats supported : AVC, H.264, H.265, MPEG4
Video streaming : Y
Web browser : Y
Weight : 420 g
White balance : ATW, AWC, Indoor, Manual, Mercury lamp, Outdoor, Sodium lamp
Wide Dynamic Range (WDR) : Y
Width : 73.1 mm
Wi-Fi : N
Windows operating systems supported : Windows 10, Windows 7, Windows 8

Zoom capability : Y