

BOSCH NIN-73013-A3AS



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : BOSCH
Part number : NIN-73013-A3AS
Représentation / réalisation :
Type : IP security camera
Système d'objectif :
Auto focus : Y
Alarm input/output : Y
Analog signal format system : NTSC, PAL
Angle of rotation : 270°
Audio formats supported : G.711, AAC-LC
Audio system full duplex : Y
Auto-tracking : Y
BNC output ports : 1
Camera pan control : Y
Camera shutter speed : 1/25 - 1/15000 s
Camera shutter type : Electronic
Camera tilt control : Y
Card reader integrated : Y
Compatible memory cards : MicroSDHC, MicroSDXC
Composite video out : 1
Connectivity technology : Wired
Day/night mode : Y
Diameter : 15.8 cm
Digital watermark : Y
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1

Flip & mirror : Y
Focal length range : 3 - 9 mm
Focus : Motorized
Focus adjustment : 1.6
Form factor : Dome
Frame rate : 60 fps
Height : 124 mm
Housing material : Aluminium, Polycarbonate (PC)
IK code : IK10
Image quality adjustment : Brightness, Contrast, Sharpness, Saturation
International Protection (IP) code : IP66
Lens viewing angle, horizontal : 32°
Lens viewing angle, vertical : 18°
Maximum memory card size : 2000 GB
Maximum resolution : 1280 x 720 pixels
Mounting type : Ceiling
Noise reduction : Y
Number of cameras : 1
Number of effective pixels (H x V) : 1280 x 720 pixels
Operating relative humidity (H-H) : 5 - 93%
Operating temperature (T-T) : -30 - 50 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Pixel counter : Y
Placement supported : Indoor & outdoor
Power consumption : 600 mA
Power consumption (max) : 7.2 W
Power source type : DC, PoE
Privacy masking : Y
Product colour : Black, White
Protection features : Scratch resistant
Region of Interest (ROI) encoding : Y
Sample rates : 8 - 16 kHz
Security algorithms : 3DES, MD5, SSL/TLS, DES, SHA-1, SHA-256
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) : 50 dB
Storage temperature (T-T) : -50 - 70 °C
Supported graphics resolutions : 1280 x 720 (HD 720), 704 x 480, 768 x 432, 512 x 288
Supported network protocols : IPv4, IPv6, UDP, TCP, HTTP, HTTPS, RTP/RTCP, IGMP V2/V3, ICMP, ICMPv6, RTSP, FTP, ARP, DHCP, APIPA (Auto-IP, link local address), NTP (SNTP), SNMP (V1, V3, MIB-II), 802.1x, DNS, DNSv6, DDNS (DynDNS.org, selfHOST.de, noip.com), SMTP, iSCSI, UPnP (SSDP), DiffServ (QoS), LLDP, SOAP, Dropbox, CHAP, digest authentication
Supported video modes : 720p
Time stamp overlay : Y
Total megapixels : 1 MP
Video formats supported : H.264, M-JPEG
Video recording : Y
Video streaming : Y
Web browser : Y
Weight : 850 g
White balance : Sodium lamp, Auto, Manual
Wide Dynamic Range (WDR) : Y
Zoom capability : Y