

AC1350 wireless dual band gigabit ceiling mount access point



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : TP-LINK
Part number : EAP610
Caractéristiques :
5 GHz : Y
Airtime Fairness (ATF) : Y
Design :
Certification : CE, FCC, RoHS
2.4 GHz : Y
AC adapter included : Y
AC input voltage : 12 V
Access Control List (ACL) : Y
Antenna type : Internal
Band steering : Y
Cabling technology : 10/100/1000Base-T(X)
DC-in jack : Y
Depth : 243 mm
Ethernet LAN (RJ-45) ports : 1
Ethernet LAN data rates : 1000 Mbit/s
Frequency band : 2.4 - 5 GHz
Harmonized System (HS) code : 85176990
Height : 64 mm
Input current : 1 A
LED indicators : Y
MAC address filtering : Y
Maximum data transfer rate : 1775 Mbit/s
Maximum data transfer rate (2.4 GHz) : 574 Mbit/s
Maximum data transfer rate (5 GHz) : 1201 Mbit/s

MIMO : Y
MIMO type : Multi User MIMO
Mounting kit : Y
Networking standards : IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Number of products included : 1 pc(s)
Operating relative humidity (H-H) : 10 - 90%
Operating temperature (T-T) : 0 - 40 °C
Package type : Box
Placement : Ceiling, Wall
Power over Ethernet (PoE) : Y
Product colour : White
Quality of Service (QoS) support : Y
Rate limiting : Y
Reset button : Y
Security algorithms : WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3, WPA3-Enterprise
Storage relative humidity (H-H) : 5 - 90%
Storage temperature (T-T) : -40 - 70 °C
Transmitting power (CE) : <20 dBm(2.4 GHz, EIRP); <23 dBm(5 GHz, EIRP)
Transmitting power (FCC) : <25 dBm (2.4 GHz); <25 dBm (5 GHz)
VLAN support : Y
Web-based management : Y
Width : 243 mm