

TP-LINK TL-ER5120 Gigabit Load Balance Broadband Router



DESCRIPTION

The TL-ER5120 Gigabit Load Balance Broadband Router from TP-LINK offers excellent data processing capabilities and multiple powerful functions including Load Balance, Access Control, IM/P2P Blocking, DoS Defense, Bandwidth Control, Session Limit and PPPoE Server, which meet the needs of small and medium enterprises, hotels and communities with large volumes of users demanding an efficient and easy-to-manage network with high security.

Main Features:

- 1 fixed gigabit WAN port, 1 fixed gigabit LAN/DMZ port and 3 freely interchangeable gigabit WAN/LAN ports
- Abundant security features including ARP Inspection, DoS Defense, URL/Keyword Domain Filter and Access Control
- Deploys One-Click restriction of IM/P2P applications to easily manage staff online behavior
- Supports PPPoE Server for the better management of internal network
- Load Balancing, automatically selects the best route according to the load
- Professional 4kV lightning protection keeps your investments as safe as possible

TECHNICAL CHARACTERISTICS

Brand : TP-LINK
Part number : ER8411
Connexion WAN :
Ethernet WAN : Y
DSL WAN : N
Caractéristiques :
Certification : CE, FCC, RoHS
3G/4G USB modem compatibility : N
AC adapter included : Y
AC input frequency : 50/60 Hz
AC input voltage : 100 - 240 V
Access Control List (ACL) : Y
Built-in processor : Y

Cabling technology : 10/100/1000Base-T(X)
Combo SFP ports quantity : 2
DC-in jack : Y
Depth : 220 mm
DHCP client : Y
DHCP server : Y
Ethernet interface type : Gigabit Ethernet
Ethernet LAN (RJ-45) ports : 8
Ethernet LAN data rates : 10,100,1000 Mbit/s
Flash memory : 256 MB
Height : 44 mm
Internal memory : 4096 MB
Internal memory type : DDR4
LED indicators : Y
Manual : Y
NAT functionality : One-to-One NAT; Multi-Net NAT; Virtual Server; Port Triggering; NAT-DMZ; FTP/H.323/SIP/IPSec/PPTP ALG; UPnP;
Networking standards : IEEE 802.1Q
Operating relative humidity (H-H) : 10 - 90%
Operating temperature (T-T) : 0 - 40 °C
Port forwarding : Y
Product colour : Black
Reset button : Y
SFP WAN : Y
SIM card slot : N
Static route : Y
Storage relative humidity (H-H) : 5 - 90%
Storage temperature (T-T) : -40 - 70 °C
Universal Plug and Play (UPnP) : Y
URL filtering : Y
USB ports quantity : 2
VLAN support : Y
Width : 440 mm