

BOSCH NIN-70122-F1A



DESCRIPTION

Features:

- 12MP / 30 fps sensor for fine details with smooth motion
- Edge or client-side dewarping for easy integration
- Intelligent Video Analysis on full panoramic overview
- Discreet and aesthetic, low-profile design
- Easy twist-click installation

NIN-70122-F1A: High-performance 12MP sensor low-profile camera for intelligent panoramic surveillance. 12MP sensor; PoE; IDNR; IAE; ROI; day/night; H.264 multiple streams; free viewing Apps; cloud services; edge dewarping; IVA; 180° lens

TECHNICAL CHARACTERISTICS

Brand : BOSCH

Part number : NIN-70122-F1A

Représentation / réalisation :

Type : IP security camera

Détails techniques :

Iris : Y

Audio formats supported : LC-AAC

Audio system full duplex : Y

Built-in HDD : N

Built-in microphone : Y

Cabling technology : 10/100Base-T(X)

Camera shutter speed : 1/15000 - 1/25 s

Camera shutter type : Electronic

Card reader integrated : Y

Compatible memory cards : SD, SDHC, SDXC

Connectivity technology : Wired

Day/night mode : Y

Depth : 158 mm

Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Firmware upgradeable : Y
Fixed focal length : 2.1 mm
Focus adjustment : 2.8
Form factor : Dome
Frame rate : 30 fps
Height : 33 mm
Lens viewing angle, horizontal : 180°
Lens viewing angle, vertical : 93°
Maximum memory card size : 2000 GB
Maximum resolution : 3648 x 2160 pixels
Minimum illumination : 0.15 lx
Mounting type : Ceiling/wall
Networking standards : IEEE 802.1x, IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u
Noise reduction : Y
Number of cameras : 1
Operating relative humidity (H-H) : 20 - 93%
Operating temperature (T-T) : -20 - 40 °C
Optical sensor size : 25.4 / 2.3 mm (1 / 2.3»)
Power consumption : 200 mA
Power over Ethernet (PoE) : Y
Power source type : PoE
Privacy masking : Y
Product colour : White
Protection features : Vandal proof
Quality of Service (QoS) support : Y
Sample rate : 16 kHz
Security algorithms : 3DES, 802.1x RADIUS, DES, HTTPS, SSL/TLS
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) : 50 dB
Storage temperature (T-T) : -20 - 60 °C
Total megapixels : 12 MP
Video compression formats : H.264, M-JPEG
Video motion detection : Y
Voice codecs : G.711
Web-based management : Y
Weight : 445 g
Wide Dynamic Range (WDR) : Y
Width : 158 mm
Wi-Fi : N