

# Eaton 9PX EBM 72V RT1U Li-Ion



## DESCRIPTION

## TECHNICAL CHARACTERISTICS

|                                                                                                                         |
|-------------------------------------------------------------------------------------------------------------------------|
| Brand : EATON                                                                                                           |
| Part number : 9PXEBM72RT1U-L                                                                                            |
| Design :                                                                                                                |
| Certification : IEC/EN 62040-1, UL 1778, CSA 22.2, IEC/EN 62040 -2, FCC Class B, CISPR22 Class B, CB report (TUV) / EAC |
| AC outlet types : C13 coupler, C19 coupler                                                                              |
| AC outlets quantity : 10 AC outlet(s)                                                                                   |
| Battery technology : Lithium-Ion (Li-Ion)                                                                               |
| Battery voltage : 72 V                                                                                                  |
| Depth : 603 mm                                                                                                          |
| Display type : LCD                                                                                                      |
| Efficiency : 93.5%                                                                                                      |
| Form factor : Rackmount/Tower                                                                                           |
| Height : 42 mm                                                                                                          |
| Input frequency : 40/70 Hz                                                                                              |
| Input operation voltage (max) : 276 V                                                                                   |
| Input operation voltage (min) : 176 V                                                                                   |
| LED indicators : Y                                                                                                      |
| Noise level : 40 dB                                                                                                     |
| Number of input phases : 1                                                                                              |
| Operating temperature (T-T) : 0 - 40 °C                                                                                 |
| Output frequency : 50/60 Hz                                                                                             |
| Output operation voltage (max) : 240 V                                                                                  |
| Output operation voltage (min) : 200 V                                                                                  |
| Output power : 2200 W                                                                                                   |
| Output power capacity : 2.2 kVA                                                                                         |
| Power plug : C20 coupler                                                                                                |
| Product colour : Black, Silver                                                                                          |

|                                               |
|-----------------------------------------------|
| Rack capacity : 1U                            |
| Rack mount kit : Y                            |
| RS-232 ports : 1                              |
| Sustainability certificates : CE, ENERGY STAR |
| UPS topology : Double-conversion (Online)     |
| USB 2:0 ports quantity : 1                    |
| USB port : Y                                  |
| Waveform : Pure sine                          |
| Weight : 17.4 kg                              |
| Width : 438 mm                                |