

Wireless AC1300 ap ceiling mount poe+



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : ENGENIUS

Part number : ECW220

Caractéristiques :

5 GHz : Y

Modulation : 16-QAM, 64-QAM, 256-QAM, 1024-QAM, BPSK, CCK, QPSK

Design :

Certification : FCC, CE, IC

2:4 GHz : Y

AC adapter included : Y

Antenna direction type : Omni-directional

Antenna features : Integrated antenna

Antenna gain level (max) : 3 dBi

Antenna type : Internal

Antennas quantity : 4

Cable lock slot : Y

Cable lock slot type : Kensington

DC-in jack : Y

Depth : 160 mm

Ethernet LAN (RJ-45) ports : 1

Ethernet LAN data rates : 10,100,1000 Mbit/s

Fit AP mode features : Mesh networking

Frequency band : 2.4 - 2.482, 5.15 - 5.25, 5.25 - 5.35, 5.47 - 5.725, 5.725 - 5.85 GHz

Harmonized System (HS) code : 85176990

Height : 33.2 mm

LED indicators : Y

MAC address filtering : Y

Management protocols : SNMP

Maximum data transfer rate : 1200 Mbit/s
Maximum data transfer rate (2.4 GHz) : 574 Mbit/s
Maximum data transfer rate (5 GHz) : 1200 Mbit/s
MIMO : Y
MIMO type : Multi User MIMO
Mounting kit : Y
Networking standards : IEEE 802.11a, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11e, IEEE 802.11g, IEEE 802.11n, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u
Number of SSID supported : 8
Operating temperature (T-T) : 0 - 40 °C
Placement : Ceiling, Wall
Power consumption (max) : 12.8 W
Power over Ethernet (PoE) : Y
Product colour : White
Quality of Service (QoS) support : Y
Quick start guide : Y
Reset button : Y
Security algorithms : WPA3, SSH, WPA2-AES, WPA2-PSK
Service Set Identifier (SSID) features : Multiple SSIDs
Spread spectrum method : OFDMA, DSSS, OFDM
Storage temperature (T-T) : -40 - 80 °C
Transmitting power : 20 dBmW
Virtual LAN features : Tagged VLAN
VLAN support : Y
Weight : 382 g
Width : 160 mm
Wi-Fi Multimedia (WMM)/(WME) : Y