



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HP
Part number : 89B62AA#AC3
Réseau :
Bluetooth : No
Auto diagnostic : Yes
Syslog : Yes
Adaptive jitter buffers : Yes
Backlight display : Yes
Cables included : LAN (RJ-45)
Call forwarding : Yes
Call hold : Yes
Call pick up : Yes
Call transfer : Yes
Call waiting : Yes
Comfort noise generation (CNG) : Yes
Conference call : Yes
Depth : 57 mm
DHCP client : Yes
Display : LCD
Display diagonal : 7.11 cm (2.8»)
Display resolution : 320 x 240 pixels
Distinctive ring : Yes
Do not disturb function : Yes
Dual-Tone Multi-Frequency (DTMF) modes : In-band
Ethernet LAN : Yes
Ethernet LAN (RJ-45) ports : 2
Ethernet LAN data rates : 10,100,1000 Mbit/s

Ethernet LAN interface type : Gigabit Ethernet
Event logging : Yes
Frequency range : 150 - 7000 Hz
Front camera : No
Handset : ITU-T P.370, TIA 504A
Handset type : Wired handset
Harmonized System (HS) code : 85171800
Headset connectivity : RJ-9
Height : 230 mm
Integrated voicemail : Yes
Keypad number of keys : 12
Lines quantity : 4 lines
Management platform : HTML5, CSS, SSL
Number of handles included : 1 pc(s)
On-hook dialling : Yes
Operating relative humidity (H-H) : 5 - 95%
Operating temperature (T-T) : 0 - 40 °C
Power over Ethernet (PoE) : Yes
Product colour : Black
Product type : IP Phone
Quality of Service (QoS) support : Yes
Quick start guide : Yes
Redialing : Yes
RJ-9 ports quantity : 1
Safety : UL 60950-1 , CE Mark , CAN/CSA C22.2 No 60950-1 , EN 60950-1 , IEC 60950-1 , AS/NZS 60950-1
SIP registrar server : Yes
Speakerphone : Yes
Speed dialling : Yes
Storage relative humidity (H-H) : -40 - 70%
Touchscreen : No
Unicode UTF-8 character support : Yes
USB 2:0 ports quantity : 1
Voice activity detection : Yes
Voice codecs : G.711, G.722, G.722.1, G.729A, G.729B, OPUS, iLBC
Volume control : Digital
WAN connection type : RJ-45
Weight : 890 g
Width : 240 mm
Wi-Fi : No