



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : PHILIPS
Part number : 65BDL3017P/00
Connectivité :
RS-232C : Y
Certificat :
Certification : CE CCC BSMI CB VCCI CECP EAC PSB EMF EnergyStar 8.0 ETL FCC, Class A
AC input frequency : 50 - 60 Hz
AC input voltage : 100 - 240 V
Audio formats supported : AAC
Batteries included : Y
Built-in speaker(s) : Y
Cables included : AC, RS-232
Card reader integrated : Y
Compatible memory cards : MicroSD (TransFlash)
Contrast ratio (dynamic) : 500000:1
Contrast ratio (typical) : 1200:1
Depth : 89.9 mm
Display brightness : 700 cd/m²
Display diagonal : 165.1 cm (65»)
Display diagonal (metric) : 164 cm
Display number of colours : 1.07 billion colours
Display resolution : 3840 x 2160 pixels
DisplayPorts quantity : 2
DVI port : Y
DVI-I ports quantity : 1
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1

Harmonized System (HS) code : 85285210
Haze rate : 25%
HD type : 4K Ultra HD
HDMI ports quantity : 3
HDMI version : 2.0
Height : 837.3 mm
Image formats supported : BMP, JPEG, PNG
Mean time between failures (MTBF) : 60000 h
Native aspect ratio : 16:9
Number of built-in speakers : 2
On Screen Display (OSD) languages : Arabic, Simplified Chinese, Traditional Chinese, Danish, German, Dutch, English, Spanish, Finnish, French, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Swedish, Turkish
Operating relative humidity (H-H) : 20 - 80%
Operating temperature (T-T) : 0 - 40 °C
Orientation : Horizontal/Vertical
Panel mounting interface : 400 x 400 mm
Panel type : VA
Pixel pitch : 0.372 x 0.372 mm
Power consumption (standby) : 0.5 W
Power consumption (typical) : 155 W
Product colour : Black
Product design : Digital signage flat panel
Purpose : Healthcare
Remote (IR) input : 1
Remote (IR) output : 1
Remote control included : Y
Response time : 8 ms
RMS rated power : 10 W
Storage relative humidity (H-H) : 5 - 95%
Storage temperature (T-T) : -20 - 60 °C
Touchscreen : N
USB port : Y
USB ports quantity : 1
USB version : 2.0
VESA mounting : Y
Video formats supported : H.264, M-JPEG, WMV3
Viewing angle, horizontal : 178°
Viewing angle, vertical : 178°
Weight : 27.8 kg
Width : 1462.3 mm