

# Eaton 93PS, 10kW frame, 10kW, sans batteries, avec MBS



## DESCRIPTION

Lowest total cost of ownership and maximum availability taking scalability, resiliency, safety, and efficiency to the next level.

The most advanced UPSs in their power range, the Eaton 91PS and 93PS are ideal for small data centers and other mission - critical applications where efficiency, reliability, safety and scalability are essential.

## TECHNICAL CHARACTERISTICS

|                                                       |
|-------------------------------------------------------|
| Brand : EATON                                         |
| Part number : 91PS10MBS                               |
| Design :                                              |
| Certification : IEC 62040-1 IEC 62040-2 IEC 62040-3   |
| Depth : 750 mm                                        |
| Efficiency : 96%                                      |
| Form factor : Tower                                   |
| Height : 950 mm                                       |
| Input current Total Harmonic Distortion (THD) : 5%    |
| Input frequency : 50/60 Hz                            |
| Input operation voltage (max) : 415 V                 |
| Input operation voltage (min) : 220 V                 |
| Input power factor : 0.99                             |
| International Protection (IP) code : IP20             |
| LED indicators : Y                                    |
| Noise level : 54 dB                                   |
| Number of input phases : 1/3                          |
| Operating altitude : 0 - 2000 m                       |
| Output power : 10000 W                                |
| Output power capacity : 10 kVA                        |
| Output power factor : 1                               |
| Output voltage Total Harmonic Distortion (THD) : 1.5% |
| Power factor : 1                                      |
| Product colour : Black                                |

|                                           |
|-------------------------------------------|
| Serial interface : Y                      |
| Serial interface type : RS-232            |
| Serial ports quantity : 1                 |
| UPS topology : Double-conversion (Online) |
| USB port : Y                              |
| Waveform : Sine                           |
| Weight : 67 kg                            |
| Width : 335 mm                            |