



DESCRIPTION

The T1931SR-B1S is based on 5-wire resistive touch technology. The price / performance ratio is ideal for the budget conscious user while quality and performance are certainly not compromised. The display includes both analogue (VGA) and digital inputs (HDMI and DisplayPort) with touchscreen connectivity via USB offering great flexibility. The flexible stand can be positioned at several angels creating a comfortable and ergonomic user experience and the integrated cable management system hides all the cables and electrical wires giving a neat and cable-free workspace. The T1931SR-B1S can be used in a variety of environments, especially recommended for shops, restaurants and industrial purposes.

TECHNICAL CHARACTERISTICS

Brand : IIYAMA
Part number : T1931SR-B1S
Représentation / réalisation :
NVIDIA G-SYNC : No
AMD FreeSync : No
Connectivité :
HDMI : Yes
Design :
Certification : CE, EAC, RoHS, ErP, WEEE, cULus, VCCI, REACH, UKCA
HDCP : Yes
AC input frequency : 50/60 Hz
AC input voltage : 100 - 240 V
Built-in camera : No
Built-in speaker(s) : Yes
Built-in USB hub : No
Cable lock slot : Yes
Cable lock slot type : Kensington
Cable management : Yes
Cables included : AC, Audio, DisplayPort, HDMI, USB
Contrast ratio (typical) : 1000:1
Depth (with stand) : 239.5 mm
Display brightness (typical) : 250 cd/m ²

Display diagonal : 48.3 cm (19»)
Display number of colours : 16.7 million colours
Display resolution : 1280 x 1024 pixels
Display technology : LCD
DisplayPorts quantity : 1
Energy consumption (SDR) per 1000 hours : 13 kWh
Energy efficiency class (SDR) : E
Energy efficiency scale : A to G
European Product Registry for Energy Labelling (EPREL) code : 1554894
HD type : SXGA
HDMI ports quantity : 1
Height (with stand) : 431.5 mm
Height adjustment : No
Horizontal scan range : 31.5 - 80 kHz
International Protection (IP) code : IP54
Market positioning : Business
Native aspect ratio : 5:4
Number of OSD languages : 7
Number of speakers : 2
On Screen Display (OSD) : Yes
On Screen Display (OSD) languages : Traditional Chinese, German, English, Estonian, French, Italian, Japanese
Package depth : 190 mm
Package height : 495 mm
Package type : Box
Package weight : 8 kg
Package width : 530 mm
Panel mounting interface : 100 x 100 mm
Panel type : IPS
Pixel pitch : 0.293 x 0.293 mm
Power consumption (off) : 0.3 W
Power consumption (standby) : 1.5 W
Power consumption (typical) : 20 W
Power supply type : Internal
Product colour : Black
Quick start guide : Yes
Response time : 14 ms
RMS rated power : 2 W
Screen shape : Flat
Tilt angle range : 90 - 5°
Touchscreen : Yes
Touchscreen technology : Resistive
USB Touch port : Yes
USB Touch ports quantity : 1
VESA mounting : Yes
VGA (D-Sub) ports quantity : 1
Viewable size, horizontal : 37.5 cm
Viewable size, vertical : 30 cm
Viewing angle, horizontal : 178°
Viewing angle, vertical : 178°
Weight (with stand) : 6 kg
Width (with stand) : 432 mm