

LG - Outdoor Display 22" 22XE1J



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : LG

Part number : 22XE1J-B

Connectivité :

RS-232C : Y

Représentation / réalisation :

HDCP : Y

AC input frequency : 50 - 60 Hz

AC input voltage : 100 - 240 V

Anti-glare screen : Y

Batteries included : Y

Built-in processor : Y

Cables included : RS-232

Computer system : Y

Computer system type : System on Chip (SoC)

Contrast ratio (typical) : 1000:1

Display brightness : 1500 cd/m²

Display depth : 65 mm

Display diagonal : 54.6 cm (21.5»)

Display height : 319.8 mm

Display number of colours : 16.7 million colours

Display resolution : 1920 x 1080 pixels

Display technology : IPS

Display weight : 8.3 kg

Display width : 557.3 mm

DVI port : N

Ethernet LAN (RJ-45) ports : 1

Harmonized System (HS) code : 85285210

Haze rate : 25%
HD type : Full HD
HDCP version : 1.4
HDMI ports quantity : 1
Internal memory : 16 GB
International Protection (IP) code : IP56
LED backlighting type : Edge-LED
Native aspect ratio : 16:9
Native refresh rate : 60 Hz
Number of OSD languages : 21
Number of speaker outputs : 1
On Screen Display (OSD) : Y
On Screen Display (OSD) languages : Arabic, Simplified Chinese, Traditional Chinese, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Greek, Italian, Japanese, Korean, Norwegian, Portuguese, Russian, Swedish, Turkish
Operating hours (hours/days) : 24/7
Operating relative humidity (H-H) : 5 - 100%
Operating system installed : Web OS
Operating temperature (T-T) : -30 - 50 °C
Package depth : 187 mm
Package height : 394 mm
Package weight : 10 kg
Package width : 632 mm
Panel mounting interface : 100 x 100 mm
Placement supported : Indoor/outdoor
Power adapter included : Y
Power consumption (off) : 0.5 W
Power consumption (standby) : 0.5 W
Power consumption (typical) : 85 W
Product colour : Black
Product design : Digital signage flat panel
Purpose : Universal
Rated lifetime : 70000 h
Remote control included : Y
Response time : 25 ms
RGB colour space : NTSC
Surface hardness : 3H
Sustainability certificates : CE, ErP
Tilt adjustment : Y
Tilt angle : 15°
Touchscreen : N
USB port : Y
USB ports quantity : 1
USB version : 2.0
VESA mounting : Y
Viewing angle, horizontal : 178°
Viewing angle, vertical : 178°
Wi-Fi : Y