

SONY- Videoprojecteur VPL-EX575- White



DESCRIPTION

Present clear, bright images, with flexible connectivity and low running costs

The VPL-EX575 projector is ideal for mid-sized classrooms and meeting rooms.

Quiet, compact and powerful, it delivers XGA images with 4,200 lumens colour light output and high 20,000:1 contrast ratio that can be seen clearly even in bright rooms and with larger projection screens, with Sony's 3LCD technology assuring natural, vivid colours. Image quality is further improved compared with previous models, with a new colour/white balance setting for crisp reproduction of on-screen text and a new 'Vivid' picture mode ensuring even richer, more vibrant colours.

The VPL-EX575 is an ideal partner for today's integrated AV/IT environments, expanding your connectivity options with dual HDMI ports and Direct USB Display connection. A convenient input label function makes life simpler, confirming on screen the name of connected devices.

Add the VPL-EX575 to a network and see presentations from up to four connected PC/Mac computers simultaneously. Slip in an optional Wi-Fi dongle and present directly wirelessly from laptops.

A range of energy-saving features plus up to 10,000 hours recommended lamp replacement time contribute to low ownership costs. Routine maintenance is quick and easy with a convenient rear lamp access feature.

TECHNICAL CHARACTERISTICS

Brand : SONY

Part number : VPL-EX575

Caractéristiques :

HDCP : Y

Autres caractéristiques :

RS-232C : Y

3D : N

AC (power) in : Y

AC input frequency : 50 - 60 Hz

AC input voltage : 100 - 240 V

Analog signal format system : NTSC, NTSC 3.58, NTSC 4.43, PAL, SECAM
Built-in display : N
Built-in speaker(s) : Y
Card reader integrated : N
Component video (YPbPr/YCbCr) in : 1
Composite video in : 1
Contrast ratio (dynamic) : 20000:1
Depth : 252 mm
DVI port : N
Ethernet LAN : Y
Ethernet LAN data rates : 10,100 Mbit/s
Focus : Manual
HDBaseT port : Y
HDMI connector type : Full-size
HDMI ports quantity : 2
Heat dissipation : 1136 BTU/h
Height : 96.2 mm
Horizontal scan range : 15 - 92 kHz
Keystone correction, vertical : -20 - 20°
Lamp power : 225 W
Lamp type : UHM
Light source type : Lamp
Market positioning : Portable
Matrix size : 1.6 cm (0.63»)
Microphone in : Y
Native aspect ratio : 4:3
Noise level (economic mode) : 29 dB
Number of built-in speakers : 1
On Screen Display (OSD) : Y
On Screen Display (OSD) languages : Arabic, Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Farsi, Finnish, French, Greek, Hungarian, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Slovenian, Swedish, Thai, Turkish, Vietnamese
Operating relative humidity (H-H) : 20 - 80%
Operating temperature (T-T) : 0 - 40 °C
Placement : Desktop
Power consumption (max) : 333 W
Power consumption (network standby) : 6.6 W
Power consumption (standby) : 0.5 W
Power consumption (typical) : 320 W
Power source : AC
Product colour : Black, White
Product type : Standard throw projector
Projection technology : 3LCD
Projector brightness : 4200 ANSI lumens
Projector brightness (economic mode) : 2300 ANSI lumens
Projector native resolution : XGA (1024x768)
Remote control included : Y
RMS rated power : 16 W
RS-232 ports : 1
Screen size compatibility : 762 - 7620 mm (30 - 300»)
Serial interface type : RS-232C
Service life of light source : 4000 h
Service life of light source (economic mode) : 10000 h
Storage relative humidity (H-H) : 20 - 80%

Storage temperature (T-T) : -10 - 60 °C
Supported video modes : 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
S-Video inputs quantity : 1
Throw ratio : 1.40 - 2.27:1
USB 2:0 ports quantity : 2
Vertical scan range : 48 - 92 Hz
VGA (D-Sub) ports quantity : 1
Weight : 4 kg
Width : 365 mm
Wi-Fi : N
Zoom capability : Y
Zoom ratio : 1.6:1
Zoom type : Manual