



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : PHILIPS	
Part number : 32BDL3511Q/00	
Connectivité :	
RS-232C	: Y
AC input frequency	: 50/60 Hz
AC input voltage	: 100 - 240 V
Audio (L/R) in	: 1
Audio (L/R) out	: 1
Audio formats supported	: AAC, HE-AAC, WMA
Batteries included	: Y
Bezel width (bottom)	: 1.72 cm
Bezel width (side)	: 1.19 cm
Bezel width (top)	: 1.19 cm
Built-in speaker(s)	: Y
Cables included	: AC, IR sensor, RS-232, USB
Contrast ratio (dynamic)	: 500000:1
Contrast ratio (typical)	: 4000:1
Display brightness	: 350 cd/m²
Display depth	: 69.1 mm
Display diagonal	: 81.3 cm (32»)
Display diagonal (metric)	: 80 cm
Display height	: 425.4 mm
Display number of colours	: 16.78 million colours
Display resolution	: 1920 x 1080 pixels
Display weight	: 5.7 kg
Display width	: 726.5 mm
DVI port	: Y

DVI-I ports quantity : 1
Energy efficiency class (SDR) : G
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Harmonized System (HS) code : 85285210
Haze rate : 2%
HD type : Full HD
HDMI input ports quantity : 2
HDMI ports quantity : 2
HDMI version : 2.0
Image formats supported : BMP, JPEG, PNG
LED backlighting type : Direct-LED
Native aspect ratio : 16:9
Number of built-in speakers : 2
Operating hours (hours/days) : 18/7
Operating relative humidity (H-H) : 20 - 80%
Operating temperature (T-T) : 0 - 40 °C
Orientation : Horizontal/Vertical
Panel life : 50000 h
Panel mounting interface : 100 x 100,200 x 200 mm
Panel type : VA
Pixel pitch : 0.36375 x 0.36375 mm
Placement supported : Indoor
Power consumption (standby) : 0.5 W
Power consumption (typical) : 45 W
Product colour : Black
Product design : Digital A-board
Purpose : Commercial
Remote (IR) input : 1
Remote (IR) output : 1
Remote control included : Y
Response time : 6.5 ms
RMS rated power : 20 W
Storage relative humidity (H-H) : 5 - 95%
Storage temperature (T-T) : -20 - 60 °C
Touchscreen : N
USB port : Y
USB ports quantity : 2
USB version : 2.0
VESA mounting : Y
Video formats supported : H.264, MPEG, WMV3
Viewing angle, horizontal : 178°
Viewing angle, vertical : 178°