

HANWHA- IP Camera 4 Mps QND-7012R



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA

Part number : QND-7012R

Représentation / réalisation :

Type : IP security camera

Réseau :

Bluetooth : N

Alarm input/output : Y

Angle of rotation : 355°

Back Light Compensation (BLC) : Y

Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)

Built-in HDD : N

Built-in microphone : Y

Camera pan control : Y

Camera shutter speed : 1/5 - 1/12000 s

Camera shutter type : Electronic

Camera tilt control : Y

Card reader integrated : Y

Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC

Composite video out : 1

Connectivity technology : Wired

Day/night mode : Y

DC output voltage : 12

Detect distance : 37.5 m

Diameter : 11 cm

Ethernet interface type : Fast Ethernet

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1

Fixed focal length : 2.8 mm
Fixed focus : Y
Flash memory : 256 MB
Flip & mirror : Y
Form factor : Dome
Frame rate : 30 fps
Height : 86 mm
Housing material : Plastic
HTTPS encryption : Y
Identify distance : 3.8 m
Infrared (IR) cut-off filter : Y
Intelligent Video Surveillance (IVS) system features : Defocus
Internal memory : 512 MB
IP address filtering : Y
LED type : IR
Lens viewing angle, diagonal : 122°
Lens viewing angle, horizontal : 107.5°
Lens viewing angle, vertical : 59.7°
Maximum aperture number : 2
Maximum memory card size : 128 GB
Maximum resolution : 2560 x 1440 pixels
Mounting type : Ceiling/wall
Networking standards : IEEE 802.1x, IEEE 802.3af
Night vision : Y
Night vision distance : 20 m
Noise reduction : Y
Number of cameras : 1
Number of lenses : 1
Number of sensors : 1
Observe distance : 15 m
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : -10 - 55 °C
Optical sensor size : 25.4 / 3 mm (1 / 3»)
Pan range : 0 - 350°
Placement supported : Indoor
Power consumption (max) : 7.1 W
Power consumption (Power over Ethernet (PoE)) : 7.9 W
Power consumption (typical) : 5.1 W
Power source type : DC, PoE
Privacy masking : Y
Product colour : White
Recognize distance : 7.5 m
Sample rate : 8 kHz
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 95%
Storage temperature (T-T) : -30 - 60 °C
Streaming method : Multicast, Unicast
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour, LLDP
Tilt angle range : 0 - 67°
Total megapixels : 4 MP
Video compression formats : H.264, H.265, M-JPEG
Video motion detection : Y

Video streaming : Y

Voice codecs : G.711, G.711ulaw, G.726

Weight : 255 g

White balance : ATW, AWC, Indoor, Manual, Outdoor

Wide Dynamic Range (WDR) : Y

Wi-Fi : N