

KL1508AIM-AXA-XG



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : ATEN

Part number : KL1508AIM-AXA-XG

AC input frequency : 50 - 60 Hz

AC input voltage : 100 - 240 V

Built-in display : Y

Console ports : PS/2, USB A, VGA (D-Sub)

Console USB ports quantity : 2

Depth : 701.2 mm

Display : LCD

Display diagonal : 43.2 cm (17»)

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1

Harmonized System (HS) code : 85176200

HD type : WUXGA

Height : 44 mm

Hot keys : Y

Housing material : Metal

Input current : 1 A

Keyboard port type : USB, PS/2

LED indicators : Y

Manual : Y

Master (outer) case gross weight : 18.5 kg

Master (outer) case height : 135 mm

Master (outer) case length : 833 mm

Master (outer) case net weight : 15.5 kg

Master (outer) case width : 668 mm

Maximum resolution : 1920 x 1200 pixels

Mouse port type : USB, PS/2
Number of computers controlled : 8
On Screen Display (OSD) : Y
Operating relative humidity (H-H) : 0 - 80%
Operating temperature (T-T) : 0 - 40 °C
Package depth : 825 mm
Package height : 135 mm
Package weight : 18.5 kg
Package width : 660 mm
Power source : AC
Product colour : Black
Products per master (outer) case : 1 pc(s)
PS/2 ports quantity : 2
Push button : Y
Quick installation guide : Y
Rack capacity : 1U
Rack mounting : Y
Scan interval : 1,255 s
Storage relative humidity (H-H) : 0 - 80%
Storage temperature (T-T) : -20 - 60 °C
USB connector type : USB Type-A
VGA (D-Sub) ports quantity : 1
Video bandwidth : 60 Hz
Video port type : VGA
Weight : 15.5 kg
Width : 480 mm