

HANWHA- Camera XNB-6000+ Face Mask Detection App



DESCRIPTION

In some workplaces, wearing a mask has now been made compulsory to contain the spread of COVID-19. Individuals not following this requirement can be detected using video analytics on-board Wisenet X Series cameras, with the ability to run reports on compliance levels.

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : XNB-6000/MSK
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : N
Audio system : 2-way
Back Light Compensation (BLC) : Y
Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Built-in HDD : N
Camera shutter speed : 2 - 1/12000 s
Camera shutter type : Electronic
Card reader integrated : Y
Compatible memory cards : SD, SDHC, SDXC
Connectivity technology : Wired
Day/night mode : Y
Depth : 147.8 mm
Digital zoom : 24x
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Flip & mirror : Y
Form factor : Bullet
Frame rate : 30 fps
Height : 66.6 mm

Highlight Compensation (HLC) : Y
Housing material : Plastic
HTTPS encryption : Y
Infrared (IR) cut-off filter : Y
IP address filtering : Y
Maximum memory card size : 512 GB
Maximum resolution : 1920 x 1080 pixels
Microphone in : Y
Minimum illumination : 0.001 lx
Mounting type : Ceiling/wall
Networking standards : IEEE 802.1x, IEEE 802.3af
Number of cameras : 1
Number of effective pixels (H x V) : 1945 x 1097 pixels
Number of lenses : 1
Number of sensors : 1
Number of users : 20 user(s)
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -10 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Placement supported : Indoor
Power source type : DC, PoE
Privacy masking : Y
Product colour : Black, Ivory
Progressive scan : Y
RS-485 ports : 1
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -50 - 60 °C
Streaming method : Multicast, Unicast
Supported network protocols : TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour
Total megapixels : 2 MP
Video compression formats : H.264, H.265, M-JPEG
Video motion detection : Y
Video streaming : Y
Voice codecs : G.711, G.711ulaw, G.726
Weight : 420 g
White balance : ATW, AWC, Indoor, Manual, Outdoor
Wide Dynamic Range (WDR) : Y
Width : 73.1 mm
Wi-Fi : N
Zoom capability : Y