

HANWHA- Camera QNO-7022R



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA

Part number : QNO-7022R

Représentation / réalisation :

Type : IP security camera

Réseau :

Bluetooth : N

Alarm input/output : Y

Alert notification type : E-mail

Anti-flicker : Y

Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)

Built-in HDD : N

Camera pan control : N

Camera shutter type : Electronic

Camera tilt control : N

Card reader integrated : Y

Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC

Connectivity technology : Wired

Day/night mode : Y

DC output voltage : 12

Detect distance : 63 m

Diameter : 7 cm

Ethernet interface type : Fast Ethernet

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1

Flash memory : 256 MB

Flip & mirror : Y

Focal length range : 4 mm

Form factor : Bullet
Frame rate : 30 fps
Housing material : Aluminium
HTTPS encryption : Y
Identify distance : 6.3 m
IK code : IK10
International Protection (IP) code : IP66
IP address filtering : Y
LED type : IR
Length : 246 mm
Lens viewing angle, diagonal : 92°
Lens viewing angle, horizontal : 78.2°
Lens viewing angle, vertical : 41.2°
Maximum aperture number : 1.6
Maximum memory card size : 128 GB
Maximum resolution : 2560 x 1440 pixels
Mirror : Y
Mounting type : Ceiling/wall
Networking standards : IEEE 802.1x
Night vision : Y
Night vision distance : 25 m
Noise reduction : Y
Number of cameras : 1
Number of lenses : 1
Number of sensors : 1
Number of users : 6 user(s)
Observe distance : 25.2 m
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : -40 - 55 °C
Optical sensor size : 25.4 / 3 mm (1 / 3»)
Password protection : Y
Password protection type : User
Placement supported : Outdoor
Power consumption (Power over Ethernet (PoE)) : 10.7 W
Power consumption (typical) : 8 W
Power source type : DC, PoE
Privacy masking : Y
Product colour : Grey
Quality of Service (QoS) support : Y
Recognize distance : 12.6 m
Sample rate : 8 kHz
Security algorithms : HTTPS, SNMPv2, SNMPv3
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 95%
Storage temperature (T-T) : -40 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 480 (VGA), 720 x 480, 800 x 448, 800 x 480 (WVGA), 800 x 600 (SVGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2560 x 1440
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour, LLDP
Total megapixels : 4 MP
Video compression formats : H.264, H.265, M-JPEG
Video formats supported : H.264, H.265, M-JPEG

Video motion detection : Y

Video streaming : Y

Voice codecs : G.711, G.711ulaw, G.726

Weight : 700 g

White balance : ATW, AWC, Indoor, Manual, Outdoor

Wide Dynamic Range (WDR) : Y

Wi-Fi : N