

Tp-link archer MR200 4G lte modem wireless AC750



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : TP-LINK
Part number : TL-MR100
Sécurité :
Stateful Packet Inspection (SPI) : Yes
Réseaux mobiles :
3G : Yes
4G : Yes
Réseau :
Dynamic DNS (DDNS) : Yes
Connexion WAN :
Ethernet WAN : Yes
DSL WAN : Yes
Caractéristiques :
Certification : CE, RoHS
3G standards : HSPA, UMTS
3G/4G USB modem compatibility : Yes
4G bands supported : 800,900,1800,1900,2100,2300,2500,2600 MHz
4G standard : LTE-TDD & LTE-FDD
AC adapter included : Yes
Antenna connector type : N-type
Antenna design : External
Antennas quantity : 2
Browser supported : Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0
Cables included : LAN (RJ-45)
Cabling technology : 10/100Base-T(X)
DC-in jack : Yes
Depth : 114 mm

DHCP client : Yes
DHCP server : Yes
DMZ support : Yes
Equivalent Isotropically Radiated Power (EIRP) (@IEEE 802.11n) : 20 dBmW
Ethernet LAN : Yes
Ethernet LAN (RJ-45) ports : 2
Ethernet LAN data rates : 10,100 Mbit/s
Ethernet LAN interface type : Fast Ethernet
Firewall : Yes
Firmware upgradeable : Yes
Guest access : Yes
Harmonized System (HS) code : 85176990
Height : 36 mm
IP address filtering : Yes
Linux operating systems supported : Yes
MAC address filtering : Yes
Mac operating systems supported : Yes
Memory card slot(s) : No
Mobile network generation : 4G
Networking standards : IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
On/off switch : Yes
Operating relative humidity (H-H) : 10 - 90%
Operating temperature (T-T) : 0 - 40 °C
Output current : 0.85 A
Output voltage : 9 V
Package depth : 161 mm
Package height : 66 mm
Package weight : 450 g
Package width : 293 mm
Port forwarding : Yes
Port triggering : Yes
Power source type : DC
Product colour : Black
Product type : Tabletop router
Quality of Service (QoS) support : Yes
Quick installation guide : Yes
Receiver sensitivity : 11g 54M: -74dBm 11n HT20: -71dBm 11n HT40: -67dBm
Reset button : Yes
Schedule access : Yes
Security algorithms : 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK
SIM card slot : Yes
Storage relative humidity (H-H) : 5 - 90%
Storage temperature (T-T) : -40 - 70 °C
Supported network protocols : IPv4, IPv6
Top Wi-Fi standard : Wi-Fi 4 (802.11n)
UMTS bands supported : 850,900,2100 MHz
Universal Plug and Play (UPnP) : Yes
USB port : No
WAN connection type : RJ-45
Width : 154 mm
Wi-Fi band : Single-band (2.4 GHz)
Wi-Fi Multimedia (WMM)/(WME) : Yes
Wi-Fi standards : 802.11b, 802.11g, Wi-Fi 4 (802.11n)

Windows operating systems supported : Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows 98SE, Windows NT, Windows Vista, Windows XP
Wireless radio : Yes
Wireless statistics : Yes
WLAN data transfer rate (max) : 300 Mbit/s
WPS push button : Yes