

ATEN PREMIUM KN1132V KVM DUAL-IP+Power CAT5 32 ports



DESCRIPTION

ATEN's 4th generation of KVM over IP switches exceed expectations. The KN1132V features superior video quality (Full HD resolution of 1920 x 1200), FIPS 140-2 with level 1 security standards and virtual media transmissions at twice the speed. The KN series provides local console and remote over IP access for users to monitor and access their entire data center over a network. In addition, it offers out-of-band access with external modem support for BIOS-level troubleshooting when the network is down.

- 1x KN1132V KVM over IP Switch
- 2x SA0142 Serial Adapters (RJ45-F to DB9-M; DTE to DCE)
- 2x LIN2-418K-E12G Power Cords
- 1x Mounting Kit
- 2x 0X12-0017-301G Lok-U-Plugs
- 1x 0X12-0017-401G Lok-U-Plug Installation Tool
- 1x Foot Pad Set (4 pcs.)
- 1x User Instructions

TECHNICAL CHARACTERISTICS

Brand : ATEN

Part number : KN1132VB-AX-G

AC input frequency : 50 - 60 Hz

AC input voltage : 100 - 240 V

Audio connections : Y

Built-in display : N

Cables included : AC

Cabling technology : 10/100/1000Base-T(X)

Cascadable : Y

Console ports : DVI-D, RJ45, USB A, VGA (D-Sub)

Console USB ports quantity : 2

Depth : 412.1 mm

DVI-D ports quantity : 1

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 36

Firmware upgradeable : Y
Harmonized System (HS) code : 85176200
HD type : WUXGA
Headphone outputs : 1
Height : 44 mm
Hot keys : Y
Housing material : Metal
Input current : 1 A
Keyboard port type : USB
LED indicators : Y
Linux operating systems supported : Y
Mac operating systems supported : Y
Manual : Y
Master (outer) case gross weight : 7.51 kg
Master (outer) case height : 130 mm
Master (outer) case length : 575 mm
Master (outer) case net weight : 6.13 kg
Master (outer) case width : 506 mm
Maximum resolution : 1920 x 1200 pixels
Mouse port type : USB
Number of computers controlled : 32
Number of microphone inputs : 1
Operating relative humidity (H-H) : 0 - 80%
Operating temperature (T-T) : 0 - 40 °C
Package depth : 575 mm
Package height : 130 mm
Package weight : 7.51 kg
Package width : 506 mm
Power consumption (typical) : 26.5 W
Power source : AC
Product colour : Black, Grey
Products per master (outer) case : 1 pc(s)
Push button : Y
Rack capacity : 1U
Rack mount kit : Y
Rack mounting : Y
Scan interval : 1,255 s
Serial port type : RJ-45
Serial ports quantity : 1
Storage temperature (T-T) : -20 - 60 °C
Sustainability certificates : RoHS
USB 2:0 Type-A hub ports quantity : 3
USB connector type : Mini-USB B, USB Type-A
USB hub : Y
VGA (D-Sub) ports quantity : 1
Video bandwidth : 60 Hz
Video port type : DVI-D/VGA
Weight : 6.13 kg
Width : 433.6 mm
Windows operating systems supported : Y