

Indus.managed PoE+ switch, 16 z 10/100/1000TX PoE+ ports and 2 z 100/1000X SFP



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : ALLIED TELESIS
Part number : AT-IE210L-10GP-60
Main features :
Network standard : Gigabit
ODI Model Layer : Layer 2
Management : WEB+SNMP+RMON+CLI
Operating environment : Industrial
Industrial : Yes
Rackmount : Yes
PoE function : Yes
Power supply : Embedded power supply
Outband console port : Yes
Temperature supported in operation : -10° to 60° C
Mounting system : Optional kit
Connectors :
Total number of ports : 11
Number of RJ-45 ports : 9
Number of fiber ports : 2
Number of BNC Ethernet ports : 0
Other ports : RS-232 RJ-45 console
RJ-45 patch cords :
Number of 10/100 ports : 0
Number of 10G ports : 0
Number of Gigabit ports : 8
Fiber optics :
Number of 100FX ports : 0
Number of SFP Gigabit ports : 0

Number of SFP+ ports : 0
Number of SFP 1G/100 ports : 2
Number of SFP 100FX ports : 0
PoE data :
PoE standard : PoE+ 802,3at 30W
PoE budget (Watts) : 125
Number of 15-Watt PoE ports : 0
Number of 30-Watt PoE+ ports : 8
Number of 60-W PoE++ ports : 0
Dimensions :
Length (mm) : 275
Width (mm) : 210
Height (mm) : 42.5