

# Eaton 9E 6000i



## DESCRIPTION

The Eaton 9E is an online double-conversion power protection at an affordable price with compact yet robust construction. This UPS is an ideal choice for industrial, medical and information technology (IT) applications and telecommunications.

### Features

- Online double conversion topology.
- Intuitive user interface with an LCD panel that provides, on a single screen, clear information about UPS status.
- Provides more real power (watts) to protect more equipment with a 0.8 power factor.
- Internal bypass and maintenance bypass are available as standards.
- Combo input (3:1 and 1:1) on the 10kVA, 15kVA, 20 kVA.
- XL models with internal supercharger for extra-long runtime.
- Communication through USB, RS232 serial or over the network with an optional network card.
- Compatible with Virtual environments (VMware, Hyper-V, Citrix Xen, Redhat).
- CE compliance certified by external agency (CB report from the TUV).

## TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : 9E6KI

### Design :

Certification : IEC/EN 62040 -2, CE, CB

AC outlet types : Terminal

Depth : 612.9 mm

Efficiency : 93%

Form factor : Tower

Height : 708.5 mm

Input frequency : 45/66 Hz

Input operation voltage (max) : 276 V

Input operation voltage (min) : 176 V

Maximum current : 82 A

Noise level : 55 dB

Operating temperature (T-T) : 0 - 40 °C

Output operation voltage (max) : 240 V

Output operation voltage (min) : 220 V

Output power : 4800 W

Output power capacity : 6 kVA

Product colour : Black

RS-232 ports : 1

Safety : IEC/EN 62040-1

Typical backup time at full load : 5 min

UPS topology : Double-conversion (Online)

USB 2:0 ports quantity : 1

Weight : 68 kg

Width : 262.4 mm