

Iiyama- Signage screen LH5575UHS-B1AG



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : Iiyama
Part number : LH5575UHS-B1AG
Connectivité :
RS-232C : Yes
Représentation / réalisation :
HDCP : Yes
Certificat :
Certification : CB, CE, TÜV-Bauart, EAC, ErP, WEEE, REACH
AC input frequency : 50 - 60 Hz
AC input voltage : 100 - 240 V
Active display area (W x H) : 1209.6 x 680.4 mm
Batteries included : Yes
Bezel width (bottom) : 1.49 cm
Bezel width (side) : 1.49 cm
Bezel width (top) : 1.49 cm
Built-in processor : Yes
Built-in speaker(s) : Yes
Cables included : AC, HDMI, RS-232
Card reader integrated : Yes
Compatible memory cards : MicroSD (TransFlash)
Contrast ratio (typical) : 1200:1
Display brightness : 500 cd/m²
Display depth : 55 mm
Display diagonal : 138.7 cm (54.6«)
Display diagonal (metric) : 139 cm
Display height : 710 mm
Display number of colours : 1.07 billion colours

Display resolution : 3840 x 2160 pixels
Display technology : LCD
Display weight : 15.2 kg
Display width : 1237.5 mm
DisplayPort version : 1.2
DisplayPorts quantity : 1
Energy consumption (SDR) per 1000 hours : 127 kWh
Energy efficiency class (SDR) : G
Energy efficiency scale : A to G
Ethernet LAN : Yes
Ethernet LAN (RJ-45) ports : 1
Harmonized System (HS) code : 85285210
Haze rate : 25%
HD type : 4K Ultra HD
HDCP version : 2.2
HDMI ports quantity : 3
HDMI version : 2.0
Horizontal scan range : 28 - 160 kHz
Housing material : Metal
Internal memory : 4 GB
Internal storage capacity : 32 GB
Maximum frame rate : 60 fps
Mean time between failures (MTBF) : 44000 h
Native aspect ratio : 16:9
Number of built-in speakers : 2
Number of OSD languages : 15
On Screen Display (OSD) : Yes
On Screen Display (OSD) languages : Simplified Chinese, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Italian, Japanese, Polish, Russian, Swedish
On-board graphics card model : ARM Mali-G52
Operating hours (hours/days) : 24/7
Operating system installed : Android 11
Operating temperature (T-T) : 0 - 40 °C
Orientation : Horizontal/Vertical
Package depth : 130 mm
Package height : 845 mm
Package weight : 20.6 kg
Package width : 1386 mm
Panel mounting interface : 400 x 400 mm
Panel type : IPS
PC Audio in : Yes
Pixel pitch : 0.315 x 0.315 mm
Placement supported : Indoor
Power consumption (off) : 0.3 W
Power consumption (standby) : 0.5 W
Power consumption (typical) : 127 W
Processor architecture : ARM Cortex-A53+Cortex-A73
Processor cores : 4
Processor family : ARM Cortex
Processor manufacturer : ARM
Product colour : Black
Product design : Digital signage flat panel
Purpose : Universal

Quick start guide : Yes
Remote (IR) input : 1
Remote (IR) output : 1
Remote control included : Yes
Response time : 8 ms
RGB colour space : sRGB
RMS rated power : 20 W
Storage temperature (T-T) : -20 - 60 °C
Sustainability certificates : RoHS
Touchscreen : No
USB port : Yes
USB ports quantity : 2
USB version : 2.0
VESA mounting : Yes
Viewing angle, horizontal : 178°
Viewing angle, vertical : 178°
Wi-Fi : Yes
Wi-Fi standards : Wi-Fi 5 (802.11ac)