



DESCRIPTION

Introducing the latest addition to Eaton’s 5 series UPS line, the Eaton 5PX G2 rackmount and tower UPS provides the maximum power possible at each power rating. The 5PX G2 UPS has power ratings ranging from 1 to 3 kVA, with low and high voltage options and offers up to four optional external battery modules for extra runtime. The 5PX G2 UPS has reduced depth to conserve space allowing for high density wallmount rack options, with the 2 to 3 kVA models.

Join the list to be first to know about the new Eaton 5PX G2 UPS.

5PX G2 UPS features include:

Deployment simplified: The 5PX G2 UPS offers mass UPS firmware upgrades without dropping the load and provides an easy startup configuration wizard simplifying your UPS setup process.

Runtime: Increased standard runtime by at least 25% on 1.5 and 2 kVA models compared to the original 5PX UPS

Stay connected, securely: Reduce risk of intrusion with the optional Gigabit Network Card (NETWORK-M2), which is the first UPS connectivity device to meet both UL and IEC cybersecurity standards

Enhanced surge protection: The 5PX G2 provides enhanced surge protection keeping your branch offices and IT closets equipment safe

TECHNICAL CHARACTERISTICS

Brand : EATON
Part number : 5PX1500RTG2
AC outlet types : NEMA 515R
AC outlets quantity : 6 AC outlet(s)
Battery technology : Sealed Lead Acid (VRLA)
Battery voltage : 48 V
Cables included : RS-232, USB cable
Depth : 447 mm
Display type : LCD

Form factor : Rackmount/Tower
Harmonized System (HS) code : 85078000
Height : 86.4 mm
Input frequency : 50/60 Hz
Input operation voltage (max) : 230 V
Input operation voltage (min) : 120 V
Output power : 1440 W
Output power capacity : 1.44 kVA
Product colour : Black, Silver
Quick installation guide : Yes
Rack capacity : 2U
Rack mount kit : Yes
RS-232 ports : 1
Serial interface : Yes
Serial interface type : RS-232
Serial ports quantity : 1
Typical backup time at full load : 5 min
Typical backup time at half load : 15 min
UPS topology : Line-Interactive
USB 2:0 ports quantity : 1
USB port : Yes
USB port type : USB Type-B
Waveform : Pure sine
Weight : 23 kg
Width : 436.9 mm