

EPDU MA 0U (C20 16A 1P) 20xC13:4xC19



DESCRIPTION

Switch and meter outlets & IT equipment across A and B feed: Combines both Switched and Metered Outlet functionality together in 1 ePDU

ePDU G3 Managed models allow complete lights-out control and metering of devices including devices powered across multiple ePDUs. They include IEC Class 1 ($\pm 1\%$) billing grade accuracy, an advanced hot-swap meter with LCD pixel display showing V, W, A and kWh, and the ability to daisy chain 8 ePDUs to share the same network connection and IP address.

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : EMAB22

Design :

Type : Single-phase

AC input frequency : 50 Hz

AC outlet types : C13 coupler, C19 coupler

AC outlets quantity : 24 AC outlet(s)

Cable colour : Black

Cable length : 3 m

Cables included : LAN (RJ-45)

Depth : 1604 mm

Dimensions (WxDxH) : 53 x 1604 x 52 mm

Display : LCD

Ethernet LAN (RJ-45) ports : 1

Firmware upgradeable : Y

Firmware upgradeable via : Network, USB

Form factor : Rackmount

Height : 52 mm

LED indicators : Y

Management protocols : SNMP, Telnet

Maximum current : 16 A

Maximum input current per phase : 16 A

| |
|---|
| Maximum power : 3700 W |
| Mounting : Vertical |
| Nominal input voltage : 230 V |
| Nominal output voltage : 230 V |
| Operating temperature (T-T) : 0 - 60 °C |
| Output connections : 20 x C13 & 4 x C19 |
| Package weight : 4.6 kg |
| PDU types : Managed |
| Power plug : C20 coupler |
| Product colour : Black |
| Rack capacity : 0U |
| Rack mount kit : Y |
| Rack mounting : Y |
| Sustainability certificates : RoHS |
| Weight : 2.5 kg |
| Width : 53 mm |