

AC1750 wireless dual band gigabit ceiling mount access point



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : TP-LINK
Part number : EAP245(5-PACK)
Caractéristiques :
5 GHz : Y
Airtime Fairness (ATF) : Y
Caractéristiques de gestion :
Syslog : Y
Design :
Certification : CE, FCC, RoHS
2.4 GHz : Y
AC adapter included : Y
AC input voltage : 48 V
Antenna direction type : Omni-directional
Antenna features : Integrated antenna
Antenna gain level (max) : 4 dBi
Antenna type : Internal
Automatic channel selection : Y
Band steering : Y
Cabling technology : 10/100/1000Base-T(X)
DC-in jack : Y
Depth : 182 mm
Ethernet LAN (RJ-45) ports : 2
Ethernet LAN data rates : 10,100,1000 Mbit/s
Frequency band : 2.4, 5 GHz
Harmonized System (HS) code : 85176990
Height : 37 mm
Input current : 1.5 A

LED indicators : Y
MAC address filtering : Y
Maximum data transfer rate : 1750 Mbit/s
Maximum data transfer rate (2:4 GHz) : 450 Mbit/s
Maximum data transfer rate (5 GHz) : 1300 Mbit/s
MIMO : Y
MIMO type : Multi User MIMO
Mounting kit : Y
Networking standards : IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x, IEEE 802.3af
Number of products included : 5 pc(s)
Number of SSID supported : 16
Operating relative humidity (H-H) : 10 - 90%
Operating temperature (T-T) : 0 - 40 °C
Placement : Ceiling, Wall
Power consumption (typical) : 12.3 W
Power over Ethernet (PoE) : Y
Product colour : White
Quality of Service (QoS) support : Y
Rate limiting : Y
Reset button : Y
Security algorithms : 64-bit WEP, 128-bit WEP, 152-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK
Storage relative humidity (H-H) : 5 - 90%
Storage temperature (T-T) : -40 - 70 °C
Transmitting power : 27 dBmW
Virtual LAN features : SSID-based VLAN assignment
VLAN support : Y
Web-based management : Y
Width : 206 mm
Wi-Fi Multimedia (WMM)/(WME) : Y
Wi-Fi roaming : Y
Wireless isolation : Y