



DESCRIPTION

The flexible Eaton 5SC UPS delivers affordable and reliable protection for small business servers, storage and network equipment. The LCD interface provides clear status of UPS key parameters and allows configuration for output voltage, audible alarm and power input sensitivity. By using Eatons Intelligent Power Manager software with the 5SC UPS you get up-to-the-minute information on the status of power in your network. The 5SC offers pure sinewave output for sensitive equipment as well as buck and boost operation to correct a wide range of input voltage variations without using batteries.

TECHNICAL CHARACTERISTICS

Brand : EATON
Part number : 5SC750
Design :
Certification : IEC 62040-2:2006 Cat C2 / CISPR22 Class A / FCC part 15 Class A
AC outlet types : NEMA 515R
AC outlets quantity : 6 AC outlet(s)
Battery technology : Sealed Lead Acid (VRLA)
Cable length : 1.8 m
Cold start : Yes
Depth : 340 mm
Display type : LCD
Efficiency : 94%
Form factor : Tower
Harmonized System (HS) code : 85078000
Height : 209 mm
Input frequency : 50/60 Hz
Input operation voltage (max) : 144 V
Input operation voltage (min) : 96 V
LED indicators : Yes
Noise level : 55 dB
Nominal input voltage : 120 V
Nominal output voltage : 120 V
Operating relative humidity (H-H) : 0 - 90%

Operating temperature (T-T) : 0 - 35 °C
Output power : 525 W
Output power capacity : 0.75 kVA
Power plug : NEMA 5-15P
Product colour : Black
RS-232 ports : 1
Safety : CE/cULus/NOM
Storage temperature (T-T) : 0 - 40 °C
Sustainability certificates : RoHS
Typical backup time at full load : 5 min
Typical backup time at half load : 13 min
USB 2:0 ports quantity : 1
Waveform : Sine
Weight : 10.5 kg
Width : 150 mm