

# 93PS-30(40)-30-4x9Ah-MBS-6



## DESCRIPTION

## TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : BD03AD306A01100000

### Design :

Certification : IEC 62040-2, IEC 62040-3

Battery capacity : 9 Ah

Battery life (max) : 10 year(s)

Battery technology : Sealed Lead Acid (VRLA)

Battery voltage : 384 V

Depth : 750 mm

Display type : LCD

Efficiency : 96%

Form factor : Tower

Height : 1750 mm

Hot-swap battery : Y

Input current Total Harmonic Distortion (THD) : 4%

Input frequency : 50/60 Hz

Input frequency converter : Y

Input operation voltage (max) : 415 V

Input operation voltage (min) : 220 V

Input power factor : 0.99

International Protection (IP) code : IP20

LED indicators : Y

Noise level : 60 dB

Number of batteries supported : 32

Number of input phases : 3

Number of output phases : 3

Output frequency : 50/60 Hz

Output operation voltage (max) : 415 V
Output operation voltage (min) : 220 V
Output power : 30000 W
Output power capacity : 30 kVA
Overload capacity (1 minute) : 125%
Overload capacity (10 minutes) : 110%
Power protection features : Overload
Product colour : Black
RS-232 ports : 1
Safety : IEC 62040-1
Total Harmonic Distortion (THD) (linear load) : 1%
Total Harmonic Distortion (THD) (non-linear load) : 5%
UPS topology : Double-conversion (Online)
USB port : Y
Width : 480 mm