



DESCRIPTION

ProLite T1731SR-W5 is based on 5 wire resistive touch technology. The price / performance ratio is ideal for the budget conscious user while quality and performance are certainly not compromised. The display inputs include both analogue and digital (VGA, HDMI and DisplayPort) with touchscreen connectivity via USB offering great flexibility. A solid and steady base supports the touchscreen with an adjustable stand offering full 90-degree angles. The ProLite T1731SR-W5 can be used in a variety of environments, especially recommended for shops, restaurants and industrial purposes. Available in black and white.

TECHNICAL CHARACTERISTICS

Brand : IIYAMA

Part number : T1731SR-W5

Certificat :

Certification : CB, CE, TÜV-Bauart, VCCI, GOST

Contrast ratio (typical) : 1000:1

Display brightness : 200 cd/m²

Display diagonal : 43.2 cm (17»)

Display resolution : 1280 x 1024 pixels

Linux operating systems supported : Yes

Native aspect ratio : 5:4

Operating relative humidity (H-H) : 20 - 80%

Operating temperature (T-T) : 0 - 40 °C

Pixel pitch : 0.264 x 0.264 mm

Product colour : White

Response time : 5 ms

Storage relative humidity (H-H) : 10 - 90%

Storage temperature (T-T) : -20 - 60 °C

Touchscreen : Yes

Viewing angle, horizontal : 170°

Viewing angle, vertical : 160°

Windows operating systems supported : Yes