



DESCRIPTION

Stand out

Inform and enthrall with a Philips Q-Line Professional Ultra HD Display. This reliable solution can be up and running as quickly as you need.

Operate, monitor and maintain with CMND and Control

Run your display network over a local (LAN) connection. CMND and Control allows you to perform vital functions like controlling inputs and monitoring display status. Whether you're in charge of one screen or 100.

FailOver ensures that content is always playing

From waiting room to meeting room, never show a blank screen. FailOver lets your Philips Professional Display switch automatically between primary and secondary inputs, ensuring that content keeps playing even if the primary source goes down. Simply set a list of alternative inputs to be sure your business is always on.

Schedule what you want, when you want with SmartPlayer

Turn your USB into a true cost-effective digital signage device. Simply save your content (video, audio, pictures) on your USB and plug into your display. Create your playlist and schedule your content via the on-screen menu, and enjoy your own playlists anytime, anywhere.

OPS slot allows for PC embedding without cabling

Integrate a full-power PC or Android-powered CRD50 module directly into your Philips Professional Display. The OPS slot contains all the connections you need to run your slot-in solution, including a power supply.

Integrated media player. Easily schedule USB content

Easily schedule content to play from USB. Your Philips Professional Display will wake from standby to play the content you want, and then return to standby once playback has finished.

TECHNICAL CHARACTERISTICS

Brand : PHILIPS

Part number : 75BDL3510Q/00

Connectivité :

RS-232C : Y
AC input frequency : 50 - 60 Hz
AC input voltage : 100 - 240 V
Built-in speaker(s) : Y
Contrast ratio (dynamic) : 500000:1
Contrast ratio (typical) : 1200:1
Depth : 69.5 mm
Display brightness : 400 cd/m²
Display diagonal : 190.5 cm (75»)»
Display diagonal (metric) : 189.3 cm
Display number of colours : 1.07 billion colours
Display resolution : 3840 x 2160 pixels
DVI port : Y
DVI-I ports quantity : 1
Energy consumption (SDR) per 1000 hours : 162 kWh
Energy efficiency class (SDR) : G
Energy efficiency scale : A to G
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
HD type : 4K Ultra HD
HDMI ports quantity : 3
HDMI version : 2.0
Height : 961.7 mm
LED backlighting type : Direct-LED
Mean time between failures (MTBF) : 50000 h
Number of built-in speakers : 2
Operating hours (hours/days) : 18/7
Operating relative humidity (H-H) : 20 - 80%
Operating temperature (T-T) : 0 - 40 °C
OPS module slot : Y
Orientation : Horizontal/Vertical
Panel mounting interface : 600 x 400 mm
PC Audio in : Y
Pixel pitch : 0.4296 x 0.4296 mm
Power consumption (typical) : 150 W
Product colour : Black
Response time : 8 ms
RMS rated power : 20 W
RS-232 interface : Y
Storage relative humidity (H-H) : 5 - 95%
Storage temperature (T-T) : -20 - 60 °C
USB port : Y
USB ports quantity : 2
USB version : 2.0
VESA mounting : Y
Viewing angle, horizontal : 178°
Viewing angle, vertical : 178°
Weight : 37.5 kg
Width : 1683.5 mm