

BOSCH- Camera Bullet 2Mps NBE-3702-AL



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : BOSCH
Part number : NBE-3702-AL
Représentation / réalisation :
Type : IP security camera
Détails techniques :
Iris : Yes
Active tampering alarm : Yes
Back Light Compensation (BLC) : Yes
Camera shutter speed : 1/25 - 1/15000 s
Camera shutter type : Electronic
Card reader integrated : Yes
Compatible memory cards : MicroSDHC, MicroSDXC
Compliance certificates : RoHS, WEEE, CE, UL, UKCA
Connectivity technology : Wired
Country of origin : Thailand
Day/night mode : Yes
Depth : 241.4 mm
Detect distance : 138 m
Digital watermark : Yes
Doesn't contain : PVC
Ethernet interface type : Fast Ethernet
Ethernet LAN : Yes
Ethernet LAN (RJ-45) ports : 1
Flash memory : 8192 MB
Flip & mirror : Yes
Focal length range : 3.3 - 10.2 mm
Form factor : Bullet

Frame rate : 30 fps
Height : 122.5 mm
Housing material : Plastic, Metal
HTTPS encryption : Yes
Human and vehicle targets classification : Yes
Identify distance : 14 m
IK code : IK10
Image quality adjustment : HDR, Sharpness, Saturation, Brightness
Infrared (IR) cut-off filter : Yes
Infra-red wavelength : 850 nm
Intelligent Video Surveillance (IVS) system features : Line crossing detection, Region entrance detection, Region exiting detection
International Protection (IP) code : IP66
LED type : IR
Lens viewing angle, horizontal : 16 - 31°
Lens viewing angle, vertical : 55 - 18°
Maximum aperture number : 1.6
Maximum memory card size : 2 TB
Maximum resolution : 1920 x 1080 pixels
Minimum illumination : 0.01 lx
Mounting type : Ceiling
Networking standards : IEEE 802.3af, IEEE 802.3at
Night vision : Yes
Night vision distance : 30 m
Number of cameras : 1
Number of lenses : 1
Number of Privacy masking areas : 8
Number of sensors : 1
Observe distance : 55 m
Operating relative humidity (H-H) : 5 - 100%
Operating temperature (T-T) : -30 - 50 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Pixel counter : Yes
Placement supported : Outdoor
Power consumption (max) : 6.7 W
Power consumption (typical) : 2.6 W
Power source type : PoE
Privacy protection : Yes
Product colour : White
Quality of Service (QoS) support : Yes
RAM capacity : 1024 MB
Recognize distance : 28 m
Security algorithms : TLS, 256-bit AES, 128-bit AES, SHA-256, MD5, SHA-1, 4096-bit RSA
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) (panoramic camera) : 55 dB
Storage relative humidity (H-H) : 5 - 95%
Storage temperature (T-T) : -50 - 70 °C
Streaming method : Multicast
Supported graphics resolutions : 1920 x 1080 (HD 1080), 512 x 288
Supported network protocols : IPv4; IPv6; UDP; TCP; HTTP; HTTPS; RTP/RTCP; IGMP V2/V3; ICMP; ICMPv6; RTSP; FTP; ARP; DHCP; APIPA (Auto-IP, link local address); NTP (SNTP); SNMP (V1, MIBII); SNMP (V3, MIBII); DNS; DNSv6; DDNS (DynDNS.org, selfHOST.de, no-ip.com); SMTP; iSCSI; UPnP (SSDP); DiffServ (QoS); LLDP; SOAP; CHAP; Digest authentication
Total megapixels : 2 MP
Video formats supported : H.264, M-JPEG, H.265, HEVC

Video intelligence analytic : Yes
Video streaming : Yes
Weight : 1.39 kg
White balance : Sodium lamp
Width : 122.5 mm
Zoom capability : Yes