



DESCRIPTION

Stylish design meets Poly pro-grade audio at a shockingly affordable price: That's what makes the Poly Edge B-Series IP Phones the genius choice for any growing business. Easy to use with illuminated keys where you need them most. Audio-enhancement technologies like Poly HD Voice and Acoustic Fence technology give you business-grade audio quality with no background noise. Service providers will love plug-and-play provisioning and cloud management capabilities. And these desk phones are hardcore reliable exactly what you need to keep customers happy. Its pure value in a low-cost business phone.

TECHNICAL CHARACTERISTICS

Brand : HP

Part number : 84C19AA#ABB

Caractéristiques du téléphone :

Full duplex : Yes

Réseau :

Auto diagnostic : Yes

Syslog : Yes

AC adapter included : Yes

AC adapter output current : 3 A

AC adapter output voltage : 5 V

Adaptive jitter buffers : Yes

Anonymous call rejection : Yes

Cables included : LAN (RJ-45)

Call forwarding : Yes

Call hold : Yes

Call log entries : 200

Call pick up : Yes

Call return : Yes

Call transfer : Yes

Call waiting : Yes

Caller ID : Yes

Comfort noise generation (CNG) : Yes

Conference call : Yes

Display : LCD
Display diagonal : 7.11 cm (2.8»)
Distinctive ring : Yes
Do not disturb function : Yes
Dual-Tone Multi-Frequency (DTMF) modes : In-band
Echo cancellation : Yes
Ethernet LAN : Yes
Ethernet LAN (RJ-45) ports : 2
Ethernet LAN data rates : 10,100 Mbit/s
Event logging : Yes
Firmware upgradeable : Yes
Handset : Yes
Handset type : Wired handset
Harmonized System (HS) code : 85171800
Headset connectivity : 3.5 mm
Hearing aid compatibility : Yes
Integrated voicemail : Yes
Keypad illumination : Yes
Lines quantity : 2 lines
Manual : Yes
Message-waiting indicator (MWI) : Yes
Microphone mute : Yes
Mounting kit : Yes
Networking standards : IEEE 802.1p, IEEE 802.3
Noise reduction : Yes
Number of handles included : 1 pc(s)
On-hook dialling : Yes
Operating relative humidity (H-H) : 5 - 95%
Operating temperature (T-T) : 0 - 40 °C
Package depth : 176 mm
Package height : 44 mm
Package weight : 960 g
Package width : 163 mm
Packet loss concealment (PLC) : Yes
Power consumption (typical) : 15 W
Power over Ethernet (PoE) : No
Product colour : Black
Product type : IP Phone
Quality of Service (QoS) support : Yes
Redialing : Yes
RJ-9 ports quantity : 1
Security algorithms : 802.1x RADIUS, HTTPS, SRTP, TLS
Speakerphone : Yes
Speed dialling : Yes
Storage temperature (T-T) : -40 - 70 °C
Sustainability certificates : ENERGY STAR
Unicode UTF-8 character support : Yes
Voice activity detection : Yes
Voice codecs : G.711, G.711alaw, G.711ulaw, G.722, G.729ab, OPUS, iLBC
Volume control : Buttons
Wall mountable : Yes