

# HANWHA- 2MP Analog Vandal-Resistant Dome Camera HCV-6080



## DESCRIPTION

## TECHNICAL CHARACTERISTICS

|                                      |
|--------------------------------------|
| Brand : HANWHA                       |
| Part number : HCV-6080               |
| Représentation / réalisation :       |
| Type : CCTV security camera          |
| Réseau :                             |
| Bluetooth : N                        |
| Certification : CE                   |
| AC input voltage : 24 V              |
| Alarm input/output : Y               |
| Analog signal format system : PAL    |
| Angle of rotation : 355°             |
| Back Light Compensation (BLC) : Y    |
| BNC output ports : 1                 |
| Built-in HDD : N                     |
| Camera pan control : Y               |
| Camera shutter speed : 1 - 1/12000 s |
| Camera shutter type : Electronic     |
| Camera tilt control : Y              |
| Closest focusing distance : 0.5 m    |
| Connectivity technology : Wired      |
| Day/night mode : Y                   |
| DC output voltage : 12               |
| Diameter : 13.7 cm                   |
| Ethernet LAN : N                     |
| Focal length range : 3.2 - 10 mm     |
| Form factor : Dome                   |
| Frame rate : 25 fps                  |

|                                                         |
|---------------------------------------------------------|
| Height : 106.1 mm                                       |
| Highlight Compensation (HLC) : Y                        |
| Housing material : Aluminium                            |
| IK code : IK10                                          |
| Infrared (IR) cut-off filter : Y                        |
| International Protection (IP) code : IP66               |
| Lens viewing angle, diagonal : 128.4°                   |
| Lens viewing angle, horizontal : 110.2°                 |
| Lens viewing angle, vertical : 55.4°                    |
| Maximum aperture number : 1.6                           |
| Maximum operating distance : 500 m                      |
| Maximum resolution : 1920 x 1080 pixels                 |
| Minimum illumination : 0.01 lx                          |
| Mounting type : Ceiling/wall                            |
| Noise reduction : Y                                     |
| Number of cameras : 1                                   |
| Number of effective pixels (H x V) : 1945 x 1097 pixels |
| Number of lenses : 1                                    |
| Number of sensors : 1                                   |
| Operating relative humidity (H-H) : 0 - 90%             |
| Operating temperature (T-T) : -30 - 55 °C               |
| Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)          |
| Pan range : 0 - 350°                                    |
| Placement supported : Outdoor                           |
| Power consumption (max) : 4.8 W                         |
| Power source type : AC, DC                              |
| Privacy masking : Y                                     |
| Product colour : Ivory                                  |
| Sensor type : CMOS                                      |
| Tilt angle range : 0 - 67°                              |
| Total megapixels : 2 MP                                 |
| Video motion detection : Y                              |
| Weight : 718 g                                          |
| White balance : ATW, AWC, Indoor, Manual, Outdoor       |
| Wide Dynamic Range (WDR) : Y                            |
| Wi-Fi : N                                               |