

Eaton 9PX 2200i RT2U Netpack Li-Ion



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : 9PX2200IRTN-L

Design :

Certification : IEC/EN 62040-1, UL 1778, CSA 22.2, IEC/EN 62040 -2, FCC Class B, CISPR22 Class B, CE /CB report (TUV) / cULus / EAC /RCM / KC

AC outlet types : C13 coupler, C19 coupler

AC outlets quantity : 10 AC outlet(s)

Battery technology : Lithium-Ion (Li-Ion)

Cable length : 1.8 m

Depth : 605 mm

Display type : LCD

Efficiency : 93.5%

Form factor : Rackmount

Harmonized System (HS) code : 85078000

Height : 86.5 mm

Input frequency : 40/70 Hz

Input operation voltage (max) : 276 V

Input operation voltage (min) : 176 V

Input power factor : 0.99

LED indicators : Status

Management card included : Y

Noise level : 40 dB

Number of input phases : 1

Operating relative humidity (H-H) : 0 - 96%

Operating temperature (T-T) : 0 - 40 °C

Output frequency : 50/60 Hz

Output operation voltage (max) : 240 V

Output operation voltage (min) : 200 V

Output power : 2200 W
Output power capacity : 2.2 kVA
Output power factor : 1
Power plug : C20 coupler
Product colour : Black, Silver
Rack capacity : 2U
Rack mount kit : Y
RS-232 ports : 1
Sustainability certificates : ENERGY STAR
Sustainability compliance : Y
UPS topology : Double-conversion (Online)
USB 2:0 ports quantity : 1
USB port : Y
Waveform : Pure sine
Weight : 25 kg
Width : 440 mm