

93PS-40(40)-40-3x9Ah-LL-MBS-6



DESCRIPTION

Eaton 91PS and 93PS provide the lowest Total Cost of Ownership and maximum availability in its power range. Whatever your mission-critical application, the Eaton 91PS and 93PS UPS offer the power performance, scalability, resiliency and efficiency you need for cost-efficient business continuity.

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : BD04A7306A01000000

Design :

Certification : CB IEC/EN 62040-2 IEC/EN 62040-1 EN 62040-3 ISO 9001 ISO 14001

Audible alarm(s) : Y

Battery capacity : 9 Ah

Depth : 750 mm

Display type : LCD

Efficiency : 99%

Efficiency (ECO mode) : 99%

Form factor : Tower

Height : 1750 mm

Hot-swap battery : Y

Input frequency : 50/60 Hz

Input operation voltage (max) : 415 V

Input operation voltage (min) : 380 V

Number of input phases : 3

Number of output phases : 3

Output frequency : 50 Hz

Output operation voltage (max) : 415 V

Output operation voltage (min) : 380 V

Output power : 40000 W

Output power capacity : 40 kVA

Output power factor : 1

Output voltage Total Harmonic Distortion (THD) : 1.5%

Power factor : 1

Product colour : Black

Sustainability certificates : CE, RoHS

Sustainability compliance : Y

Typical backup time at full load : 5 min

UPS topology : Double-conversion (Online)

Waveform : Sine

Weight : 449 kg

Width : 480 mm